

www.millsteelframing.com | 2905 Lucerne Dr. SE Grand Rapids, MI 49546 | (812) 670-4195

## Structural Stud

# 362S300-54G90


Product Description	16 GA GALV 3.62" WEB X 3.00" FLANGE C-STUD .054 MIN GAUGE G90
Coating	G90
Physical Properties	
Design Thickness (in)	0.0566
Minimum Thickness (in)	0.0538
Web Width (in)	3.6250
Flange Width (in)	3.0000
Stiffening Lip (in)	0.6250
Yield Strength (ksi)	50.0000

Gross Section Properties	
Cross Sectional Area (A)	0.592
Weight of Member (lb/ft)	2.01
Section Modulus (Sx)	0.767
Moment of Inertia (lx)	1.391
Radius of Gyration (Rx)	1.533
Gross Moment of Inertia (ly)	0.734
Gross Radium of Gyration (Ry)	1.114

<b>Effective Section Properties</b>	
Moment of Inertia for deflection (lxe)	1.295
Section Modulus (Sxe)	0.529
Allowable Bending moment (Ma)	15.83
Allowable shear force in web (U)(Vag)	3372
Allowable shear at punch (Vanet)	1016

Torsional Properties	
St. Venant torsion constant (J x 1000)	0.632
Warping constant (Cw)	2.316
Distance from shear center to neutral axis (Xo)	-2.659
Radii of gyration (Ro)	3.265
Torsional flexural constant (Beta)	0.337

#### **Punch Out**



### ASTM & Code Standards

- AISI S100-12 & ICC ES ESR-4062
- Framing meets ASTM A1003, A653 & C955

#### Notes

- 1. Calculated properties are based on AISI S100-16, North American Specification for Design of Cold-Formed Steel Structural Members.
- 2. The centerline bend radius is based on inside corner radii shown in thickness chart.
- 3. Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A3.3.2.
- 4. Tabulated gross properties are based on fullunreduced cross section of the studs, away from punch outs.
- 5. For deflection calculations, use the effective moment of inertia.
- 6. Allowable moment includes cold-work of forming.

### Mill Steel Framing LEED Green Credits

MR Credit 2	<ul> <li>ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable</li> </ul>
MR Credit 4	Recycled Content – Mill Steel Framing products contain no less than 25.5% post-consumer
	and 6.8% pre-consumer recycled content
MR Credit 5	• Regional Materials – Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas
V4 MR Credits	Building Product Disclosure and Optimization EPD (1 point)
	Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point)

