

## Structural Stud 400S200-54G90

<b>Product Description</b>	<b>16 GA GALV 4" WEB X 2.00" FLANGE C-STUD .054 MIN GAUGE G90</b>
<b>Coating</b>	<b>G90</b>
<b>Physical Properties</b>	
Design Thickness (in)	0.0566
Minimum Thickness (in)	0.0538
Web Width (in)	4.0000
Flange Width (in)	2.0000
Stiffening Lip (in)	0.6250
Yield Strength (ksi)	50.0000



### Gross Section Properties

Cross Sectional Area (A)	0.500
Weight of Member (lb/ft)	1.70
Section Modulus (Sx)	0.646
Moment of Inertia (Ix)	1.292
Radius of Gyration (Rx)	1.608
Gross Moment of Inertia (Iy)	0.287
Gross Radium of Gyration (Ry)	0.758


### Effective Section Properties

Moment of Inertia for deflection (Ixe)	1.292
Section Modulus (Sxe)	0.549
Allowable Bending moment (Ma)	16.43
Allowable shear force in web (U)(Vag)	3372
Allowable shear at punch (Vanet)	1223

### Torsional Properties

St. Venant torsion constant (J x 1000)	0.534
Warping constant (Cw)	1.083
Distance from shear center to neutral axis (Xo)	-1.662
Radii of gyration (Ro)	2.433
Torsional flexural constant (Beta)	0.534

### Punch Out



### ASTM & Code Standards

- AISI S100-12 & ICC ES ESR-4062
- Framing meets ASTM A1003, A653 & C955

### Notes

1. Calculated properties are based on AISI S100-16, North American Specification for Design of Cold-Formed Steel Structural Members.
2. The centerline bend radius is based on inside corner radii shown in thickness chart.
3. Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A3.3.2.
4. Tabulated gross properties are based on full-unreduced cross section of the studs, away from punch outs.
5. For deflection calculations, use the effective moment of inertia.
6. Allowable moment includes cold-work of forming.

## Mill Steel Framing LEED Green Credits

- |                      |  |
|----------------------|--|
| <b>MR Credit 2</b>   | • ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable   |
| <b>MR Credit 4</b>   | • Recycled Content – Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content |
| <b>MR Credit 5</b>   | • Regional Materials – Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas                               |
| <b>V4 MR Credits</b> | • Building Product Disclosure and Optimization EPD (1 point)   |
|                      | • Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point)                                       |

