

www.millsteelframing.com | 2905 Lucerne Dr. SE Grand Rapids, MI 49546 | (812) 670-4195

## Structural Stud 1000S200-54G90

Product Description 16 GA GALV 10.00" WEB x 2.00"

FLANGE C-STUD .054 MIN GAUGE

G90

Coating G90

**Physical Properties** 

Design Thickness (in)0.0566Minimum Thickness (in)0.0538Web Width (in)10.0000Flange Width (in)2.0000Stiffening Lip (in)0.6250Yield Strength (ksi)50.0000




Gross Section Properties	
Cross Sectional Area (A)	0.839
Weight of Member (lb/ft)	2.86
Section Modulus (Sx)	2.256
Moment of Inertia (lx)	11.282
Radius of Gyration (Rx)	3.666
Gross Moment of Inertia (ly)	0.378
Gross Radium of Gyration (Ry)	0.671

Effective Section Properties	
Moment of Inertia for deflection (lxe)	10.770
Section Modulus (Sxe)	1.705
Allowable Bending moment (Ma)	51.05
Allowable shear force in web (U)(Vag)	1661
Allowable shear at punch (Vanet)	1661

Torsional Properties	
St. Venant torsion constant (J x 1000)	0.896
Warping constant (Cw)	7.665
Distance from shear center to neutral axis (Xo)	-1.135
Radii of gyration (Ro)	3.896
Torsional flexural constant (Beta)	0.915

### **Punch Out**



# ASTM & Code Standards

- AISI S100-12 & ICC ES ESR-4062
- Framing meets ASTM A1003, A653 & C955

#### **Notes**

- Calculated properties are based on AISI S100-16, North American Specification for Design of Cold-Formed Steel Structural Members.
- 2. The centerline bend radius is based on inside corner radii shown in thickness chart.
- 3. Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A3.3.2.
- 4. Tabulated gross properties are based on fullunreduced cross section of the studs, away from punch outs.
- 5. For deflection calculations, use the effective moment of inertia.
- 6. Allowable moment includes cold-work of forming.

### Mill Steel Framing LEED Green Credits

MR Credit 2 MR Credit 4 ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable

• Recycled C

 Recycled Content – Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content

MR Credit 5 V4 MR Credits • Regional Materials - Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas

**dits** • Building Product Disclosure and Optimization EPD (1 point)

• Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point)

