

www.millsteelframing.com │ 2905 Lucerne Dr. SE Grand Rapids, MI 49546 │ (812) 670-4195

Structural Stud 362S137-43

Product Description 18 GA GALV 3.62" WEB x 1.37"

FLANGE C-STUD .043 MIN

GAUGE

Coating G60

Physical Properties

 Design Thickness (in)
 0.0451

 Minimum Thickness (in)
 0.0428

 Web Width (in)
 3.6250

 Flange Width (in)
 1.3750

 Stiffening Lip (in)
 0.3750

 Yield Strength (ksi)
 33.0000




Gross Section Properties	
Cross Sectional Area (A)	0.306
Weight of Member (lb/ft)	1.04
Section Modulus (Sx)	0.340
Moment of Inertia (lx)	0.616
Radius of Gyration (Rx)	1.419
Gross Moment of Inertia (ly)	0.075
Gross Radium of Gyration (Ry)	0.497

Effective Section Properties	
Moment of Inertia for deflection (lxe)	0.616
Section Modulus (Sxe)	0.320
Allowable Bending moment (Ma)	6.33
Allowable shear force in web (U)(Vag)	1739
Allowable shear at punch (Vanet)	676

Torsional Properties	
St. Venant torsion constant (J x 1000)	0.207
Warping constant (Cw)	0.208
Distance from shear center to neutral axis (Xo)	-0.991
Radii of gyration (Ro)	1.801
Torsional flexural constant (Beta)	0.697

Punch Out



ASTM & Code Standards

- AISI S100-12 & ICC ES ESR-4062
- Framing meets ASTM A1003, A653 & C955

Notes

- Calculated properties are based on AISI S100-16, North American Specification for Design of Cold-Formed Steel Structural Members.
- 2. The centerline bend radius is based on inside corner radii shown in thickness chart.
- 3. Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A3.3.2.
- 4. Tabulated gross properties are based on fullunreduced cross section of the studs, away from punch outs.
- 5. For deflection calculations, use the effective moment of inertia.
- 6. Allowable moment includes cold-work of forming.

Mill Steel Framing LEED Green Credits

MR Credit 2 MR Credit 4

- ConstructionWaste Management Mill Steel Framing steel framing is 100% recyclable
- Recycled Content Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content

MR Credit 5

• Regional Materials - Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas

V4 MR Credits • Building Product Disclosure and Optimization EPD (1 point)

· Materials Ingredients (1 point) - Construction and Demolition Waste Management (1 point)

