

www.millsteelframing.com | 2905 Lucerne Dr. SE Grand Rapids, MI 49546 | (812) 670-4195

# Structural Stud 362S162-43G90


Product Description	18 GA GALV 3.62" WEB x 1.62" FLANGE C-STUD .043 MIN GAUGE G90
Coating	G90
Physical Properties	
Design Thickness (in)	0.0451
Minimum Thickness (in)	0.0428
Web Width (in)	3.6250
Flange Width (in)	1.6250
Stiffening Lip (in)	0.5000
Yield Strength (ksi)	33.0000

Gross Section Properties	
Cross Sectional Area (A)	0.340
Weight of Member (lb/ft)	1.16
Section Modulus (Sx)	0.392
Moment of Inertia (lx)	0.710
Radius of Gyration (Rx)	1.445
Gross Moment of Inertia (ly)	0.127
Gross Radium of Gyration (Ry)	0.611

<b>Effective Section Properties</b>	
Moment of Inertia for deflection (lxe)	0.710
Section Modulus (Sxe)	0.372
Allowable Bending moment (Ma)	7.34
Allowable shear force in web (U)(Vag)	1739
Allowable shear at punch (Vanet)	676

Torsional Properties	
St. Venant torsion constant (J x 1000)	0.230
Warping constant (Cw)	0.376
Distance from shear center to neutral axis (Xo)	-1.297
Radii of gyration (Ro)	2.036
Torsional flexural constant (Beta)	0.594

### **Punch Out**



# **ASTM & Code Standards**

- AISI \$100-12 & ICC ES ESR-4062
- Framing meets ASTM A1003, A653 & C955

### Notes

- 1. Calculated properties are based on AISI S100-16, North American Specification for Design of Cold-Formed Steel Structural Members.
- 2. The centerline bend radius is based on inside corner radii shown in thickness chart.
- 3. Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A3.3.2.
- 4. Tabulated gross properties are based on fullunreduced cross section of the studs, away from punch outs.
- 5. For deflection calculations, use the effective moment of inertia.
- 6. Allowable moment includes cold-work of forming.

# **Mill Steel Framing LEED Green Credits**

MR Credit 2	<ul> <li>ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable</li> </ul>
MR Credit 4	<ul> <li>Recycled Content – Mill Steel Framing products contain no less than 25.5% post-consumer</li> </ul>
	and 6.8% pre-consumer recycled content
MR Credit 5	• Regional Materials – Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas
V4 MR Credits	Building Product Disclosure and Optimization EPD (1 point)
	• Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point)

