

www.millsteelframing.com | 2905 Lucerne Dr. SE Grand Rapids, MI 49546 | (812) 670-4195

## **Structural Stud**

Structural Stud	362S200-43
Product Description	18 GA GALV 3.62" WEB x 2.00" FLANGE C-STUD   .043 MIN GAUGE
Coating	G60
Physical Properties	
Design Thickness (in)	0.0451
Minimum Thickness (in)	0.0428
Web Width (in)	3.6250

2.0000 0.6250 33.0000


Design Thickness (in)
Minimum Thickness (in)
Web Width (in)
Flange Width (in)
Stiffening Lip (in)
Yield Strength (ksi)

Gross Section Properties	
Cross Sectional Area (A)	0.385
Weight of Member (lb/ft)	1.31
Section Modulus (Sx)	0.461
Moment of Inertia (lx)	0.836
Radius of Gyration (Rx)	1.474
Gross Moment of Inertia (ly)	0.227
Gross Radium of Gyration (Ry)	0.767

Effective Section Properties	
Moment of Inertia for deflection (lxe)	0.836
Section Modulus (Sxe)	0.427
Allowable Bending moment (Ma)	8.43
Allowable shear force in web (U)(Vag)	1739
Allowable shear at punch (Vanet)	676

Torsional Properties	
St. Venant torsion constant (J x 1000)	0.261
Warping constant (Cw)	0.734
Distance from shear center to neutral axis (Xo)	-1.729
Radii of gyration (Ro)	2.398
Torsional flexural constant (Beta)	0.480

# **Punch Out**



### **ASTM & Code Standards**

- AISI \$100-12 & ICC ES ESR-4062
- Framing meets ASTM A1003, A653 & C955

#### Notes

- 1. Calculated properties are based on AISI S100-16, North American Specification for Design of Cold-Formed Steel Structural Members.
- 2. The centerline bend radius is based on inside corner radii shown in thickness chart.
- 3. Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A3.3.2.
- 4. Tabulated gross properties are based on fullunreduced cross section of the studs, away from punch outs.
- 5. For deflection calculations, use the effective moment of inertia.
- 6. Allowable moment includes cold-work of forming.

### **Mill Steel Framing LEED Green Credits**

MR Credit 2	<ul> <li>ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable</li> </ul>
MR Credit 4	Recycled Content – Mill Steel Framing products contain no less than 25.5% post-consumer
	and 6.8% pre-consumer recycled content
MR Credit 5	• Regional Materials – Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas
V4 MR Credits	Building Product Disclosure and Optimization EPD (1 point)
	• Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point)

