

www.millsteelframing.com │ 2905 Lucerne Dr. SE Grand Rapids, MI 49546 │ (812) 670-4195

Structural Stud 600S137-43G90

18 GA GALV 6.00" WEB x 1.37" **Product Description**

FLANGE C-STUD .043 MIN GAUGE

G90

Coating G90

Physical Properties

Design Thickness (in) 0.0451 Minimum Thickness (in) 0.0428 Web Width (in) 6.0000 Flange Width (in) 1.3750 Stiffening Lip (in) 0.3750 Yield Strength (ksi) 33.0000




Gross Section Properties	
Cross Sectional Area (A)	0.413
Weight of Member (lb/ft)	1.41
Section Modulus (Sx)	0.681
Moment of Inertia (lx)	2.042
Radius of Gyration (Rx)	2.224
Gross Moment of Inertia (ly)	0.087
Gross Radium of Gyration (Ry)	0.459

Effective Section Properties	
Moment of Inertia for deflection (lxe)	2.041
Section Modulus (Sxe)	0.645
Allowable Bending moment (Ma)	12.74
Allowable shear force in web (U)(Vag)	1416
Allowable shear at punch (Vanet)	1240

Torsional Properties	
St. Venant torsion constant (J x 1000)	0.280
Warping constant (Cw)	0.633
Distance from shear center to neutral axis (Xo)	-0.796
Radii of gyration (Ro)	2.406
Torsional flexural constant (Beta)	0.890

Punch Out



ASTM & Code Standards

- AISI S100-12 & ICC ES ESR-4062
- Framing meets ASTM A1003, A653 & C955

Notes

- 1. Calculated properties are based on AISI S100-16, North American Specification for Design of Cold-Formed Steel Structural Members.
- 2. The centerline bend radius is based on inside corner radii shown in thickness chart.
- 3. Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A3.3.2.
- Tabulated gross properties are based on fullunreduced cross section of the studs, away from punch outs.
- 5. For deflection calculations, use the effective moment of inertia.
- 6. Allowable moment includes cold-work of forming.

Mill Steel Framing LEED Green Credits

MR Credit 2 MR Credit 4

- ConstructionWaste Management Mill Steel Framing steel framing is 100% recyclable
- Recycled Content Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content
 - · Regional Materials Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas

MR Credit 5 V4 MR Credits

• Building Product Disclosure and Optimization EPD (1 point)

· Materials Ingredients (1 point) - Construction and Demolition Waste Management (1 point)

