

www.millsteelframing.com | 2905 Lucerne Dr. SE Grand Rapids, MI 49546 | (812) 670-4195

# Structural Stud 362S162-33G90

Product Description 20 GA GALV 3.62" WEB x 1.62"

FLANGE C-STUD .033 MIN GAUGE

G90

Coating G90

**Physical Properties** 

Design Thickness (in)0.0346Minimum Thickness (in)0.0329Web Width (in)3.6250Flange Width (in)1.6250Stiffening Lip (in)0.5000Yield Strength (ksi)33.0000




Gross Section Properties	
Cross Sectional Area (A)	0.262
Weight of Member (lb/ft)	0.89
Section Modulus (Sx)	0.304
Moment of Inertia (lx)	0.551
Radius of Gyration (Rx)	1.450
Gross Moment of Inertia (ly)	0.099
Gross Radium of Gyration (Ry)	0.616

Effective Section Properties	
Moment of Inertia for deflection (lxe)	0.551
Section Modulus (Sxe)	0.268
Allowable Bending moment (Ma)	5.29
Allowable shear force in web (U)(Vag)	1024
Allowable shear at punch (Vanet)	521

Torsional Properties	
St. Venant torsion constant (J x 1000)	0.105
Warping constant (Cw)	0.297
Distance from shear center to neutral axis (Xo)	-1.308
Radii of gyration (Ro)	2.048
Torsional flexural constant (Beta)	0.592

### **Punch Out**



# ASTM & Code Standards

- AISI S100-12 & ICC ES ESR-4062
- Framing meets ASTM A1003, A653 & C955

#### **Notes**

- Calculated properties are based on AISI S100-16, North American Specification for Design of Cold-Formed Steel Structural Members.
- 2. The centerline bend radius is based on inside corner radii shown in thickness chart.
- 3. Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A3.3.2.
- 4. Tabulated gross properties are based on fullunreduced cross section of the studs, away from punch outs.
- 5. For deflection calculations, use the effective moment of inertia.
- 6. Allowable moment includes cold-work of forming.

## **Mill Steel Framing LEED Green Credits**

MR Credit 2 MR Credit 4

- ConstructionWaste Management Mill Steel Framing steel framing is 100% recyclable
- Recycled Content Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content

MR Credit 5

• Regional Materials - Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas

**V4 MR Credits** • Building Product Disclosure and Optimization EPD (1 point)

• Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point)

