

www.millsteelframing.com │ 2905 Lucerne Dr. SE Grand Rapids, MI 49546 │ (812) 670-4195

#### Structural Stud 600S137-33

20 GA GALV 6.00" WEB x 1.37" **Product Description** 

FLANGE C-STUD .033 MIN

**GAUGE** 

Coating G60

**Physical Properties** 

Design Thickness (in) 0.0346 Minimum Thickness (in) 0.0329 Web Width (in) 6.0000 Flange Width (in) 1.3750 Stiffening Lip (in) 0.3750 Yield Strength (ksi) 33.0000




| Gross Section Properties      |       |
|-------------------------------|-------|
| Cross Sectional Area (A)      | 0.318 |
| Weight of Member (lb/ft)      | 1.08  |
| Section Modulus (Sx)          | 0.528 |
| Moment of Inertia (lx)        | 1.583 |
| Radius of Gyration (Rx)       | 2.230 |
| Gross Moment of Inertia (ly)  | 0.069 |
| Gross Radium of Gyration (Ry) | 0.464 |

| Effective Section Properties           |       |
|--|-------|
| Moment of Inertia for deflection (lxe) | 1.548 |
| Section Modulus (Sxe)                  | 0.455 |
| Allowable Bending moment (Ma)          | 8.98  |
| Allowable shear force in web (U)(Vag)  | 638   |
| Allowable shear at punch (Vanet)       | 638   |

| Torsional Properties                            |        |
|---|--------|
| St. Venant torsion constant (J x 1000)          | 0.127  |
| Warping constant (Cw)                           | 0.500  |
| Distance from shear center to neutral axis (Xo) | -0.807 |
| Radii of gyration (Ro)                          | 2.416  |
| Torsional flexural constant (Beta)              | 0.889  |

### **Punch Out**



# **ASTM & Code Standards**

- AISI S100-12 & ICC ES ESR-4062
- Framing meets ASTM A1003, A653 & C955

#### **Notes**

- 1. Calculated properties are based on AISI S100-16, North American Specification for Design of Cold-Formed Steel Structural Members.
- 2. The centerline bend radius is based on inside corner radii shown in thickness chart.
- 3. Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A3.3.2.
- 4. Tabulated gross properties are based on fullunreduced cross section of the studs, away from punch outs.
- 5. For deflection calculations, use the effective moment of inertia.
- 6. Allowable moment includes cold-work of forming.

# Mill Steel Framing LEED Green Credits

MR Credit 2 MR Credit 4

- ConstructionWaste Management Mill Steel Framing steel framing is 100% recyclable
- Recycled Content Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content

MR Credit 5

· Regional Materials - Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas

• Building Product Disclosure and Optimization EPD (1 point) V4 MR Credits

· Materials Ingredients (1 point) - Construction and Demolition Waste Management (1 point)

