

www.millsteelframing.com │ 2905 Lucerne Dr. SE Grand Rapids, MI 49546 │ (812) 670-4195

Structural Track 400T200-68G90

Product Description 14 GA GALV 4.00" WEB x 2.00"


FLANGE TRACK .068 MIN

GAUGE G90

G90 Coating

Physical Properties

Design Thickness (in) 0.0713 Minimum Thickness (in) 0.0677 Web Width (in) Flange Width (in) 2 Yield Strength (ksi) 50



Gross Section Properties	
Cross Sectional Area (A)	0.569
Weight of Member (lb/ft)	1.94
Section Modulus (Sx)	0.761
Moment of Inertia (lx)	1.617
Radius of Gyration (Rx)	1.685
Gross Moment of Inertia (ly)	0.227
Gross Radium of Gyration (Ry)	0.632

Effective Section Properties	
Moment of Inertia for deflection (lxe)	1.412
Section Modulus (Sxe)	0.549
Allowable Bending moment (Ma)	16.43
Allowable shear force in web (U)(Vag)	5205

Torsional Properties	
St. Venant torsion constant (J x 1000)	0.9647
Warping constant (Cw)	0.702
Distance from shear center to neutral axis (Xo)	-1.209
Radii of gyration (Ro)	2.168
Torsional flexural constant (Beta)	0.689

ASTM & Code Standards

- AISI S100-12 & ICC ES ESR-4062
- Framing meets ASTM A1003, A653 & C955

Notes

- 1. Calculated properties are based on AISI S100-16, North American Specification for Design of Cold-Formed Steel Structural Members.
- 2. The centerline bend radius is based on inside corner radii shown in thickness chart.
- 3. Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A3.3.2.
- Tabulated gross properties are based on full-unreduced cross section of the studs, away from punchouts.
- 5. For deflection calculations, use the effective moment of inertia.
- 6. Allowable moment includes cold-work of forming.
- 7. Web depth for track sections is equal to the nominal height plus 2 times the design thickness plus the bend radius. Hems on non-structural rack sections are ignored.

Mill Steel Framing LEED Green Credits

MR Credit 2 MR Credit 4

- ConstructionWaste Management Mill Steel Framing steel framing is 100% recyclable
- Recycled Content Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content

· Regional Materials - Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas

MR Credit 5

V4 MR Credits • Building Product Disclosure and Optimization EPD (1 point)

· Materials Ingredients (1 point) - Construction and Demolition Waste Management (1 point)

