

www.millsteelframing.com │ 2905 Lucerne Dr. SE Grand Rapids, MI 49546 │ (812) 670-4195

Structural Track 1200T200-54

Product Description 16 GA GALV 12.00" WEB x

2.00" FLANGE TRACK .054 MIN

GAUGE

Coating G60

Physical Properties

Design Thickness (in) 0.0566
Minimum Thickness (in) 0.0538
Web Width (in) 12
Flange Width (in) 2
Yield Strength (ksi) 50



Gross Section Properties	
Cross Sectional Area (A)	0.905
Weight of Member (lb/ft)	3.08
Section Modulus (Sx)	2.7
Moment of Inertia (lx)	16.47
Radius of Gyration (Rx)	4.266
Gross Moment of Inertia (ly)	0.236
Gross Radium of Gyration (Ry)	0.51

Effective Section Properties	
Moment of Inertia for deflection (lxe)	12.965
Section Modulus (Sxe)	1.35
Allowable Bending moment (Ma)	40.42
Allowable shear force in web (U)(Vag)	1354

Torsional Properties	
St. Venant torsion constant (J x 1000)	0.9663
Warping constant (Cw)	6.714
Distance from shear center to neutral axis (Xo)	-0.73
Radii of gyration (Ro)	4.358
Torsional flexural constant (Beta)	0.972

ASTM & Code Standards

- AISI S100-12 & ICC ES ESR-4062
- Framing meets ASTM A1003, A653 & C955

Notes

- Calculated properties are based on AISI S100-16, North American Specification for Design of Cold-Formed Steel Structural Members.
- 2. The centerline bend radius is based on inside corner radii shown in thickness chart.
- 3. Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A3.3.2.
- 4. Tabulated gross properties are based on full-unreduced cross section of the studs, away from punchouts.
- 5. For deflection calculations, use the effective moment of inertia.
- 6. Allowable moment includes cold-work of forming.
- 7. Web depth for track sections is equal to the nominal height plus 2 times the design thickness plus the bend radius. Hems on non-structural rack sections are ignored.

Mill Steel Framing LEED Green Credits

MR Credit 2

- ConstructionWaste Management Mill Steel Framing steel framing is 100% recyclable
- Recycled Content Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content

MR Credit 5

• Regional Materials - Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas

V4 MR Credits • Building Product Disclosure and Optimization EPD (1 point)

· Materials Ingredients (1 point) - Construction and Demolition Waste Management (1 point)

