

www.millsteelframing.com | 2905 Lucerne Dr. SE Grand Rapids, MI 49546 | (812) 670-4195

Structural Track 1000T150-43

Product Description	18 GA GALV 10.00" WEB X 1.50" FLANGE TRACK .043 MIN GAUGE
Coating	G60
Physical Properties Design Thickness (in) Minimum Thickness (in) Web Width (in) Flange Width (in) Yield Strength (ksi)	0.0451 0.0428 10 1.5 33

Gross Section Properties	
Cross Sectional Area (A)	0.586
Weight of Member (lb/ft)	1.99
Section Modulus (Sx)	1.419
Moment of Inertia (lx)	7.21
Radius of Gyration (Rx)	3.508
Gross Moment of Inertia (ly)	0.08
Gross Radium of Gyration (Ry)	0.37

Effective Section Properties		
Moment of Inertia for deflection (lxe)	6.197	
Section Modulus (Sxe)	0.837	
Allowable Bending moment (Ma)	16.54	
Allowable shear force in web (U)(Vag)	822	

Torsional Properties	
St. Venant torsion constant (J x 1000)	0.3972
Warping constant (Cw)	1.612
Distance from shear center to neutral axis (Xo)	-0.513
Radii of gyration (Ro)	3.565
Torsional flexural constant (Beta)	0.979

ASTM & Code Standards

- AISI \$100-12 & ICC ES ESR-4062
- Framing meets ASTM A1003, A653 & C955

Notes

- Calculated properties are based on AISI S100-16, North American Specification for Design of Cold-Formed Steel Structural Members.
- 2. The centerline bend radius is based on inside corner radii shown in thickness chart.
- 3. Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A3.3.2.
- 4. Tabulated gross properties are based on full-unreduced cross section of the studs, away from punchouts.
- 5. For deflection calculations, use the effective moment of inertia.
- 6. Allowable moment includes cold-work of forming.
- 7. Web depth for track sections is equal to the nominal height plus 2 times the design thickness plus the bend radius. Hems on non-structural rack sections are ignored.

Mill Steel Framing LEED Green Credits

MR Credit 2	 ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable
MR Credit 4	• Recycled Content – Mill Steel Framing products contain no less than 25.5% post-consumer
	and 6.8% pre-consumer recycled content
MR Credit 5	• Regional Materials – Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas
V4 MR Credits	Building Product Disclosure and Optimization EPD (1 point)
	• Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point)

