

www.millsteelframing.com │ 2905 Lucerne Dr. SE Grand Rapids, MI 49546 │ (812) 670-4195

Utility Angles 1.5X1.5ANGLE20G90

1.5" X 1.5" ANGLE 20 GAUGE **Product Description**

G90 COATED

G90 Coating

*Also available in G90 coating

Physical Properties

Design Thickness (in) 0.0312 Minimum Thickness (in) 0.0296 Leg 1 Length (in) 1.5 Leg 2 Length (in) 1.5 Yield Strength (ksi) 33



Note

Standard stock length is 10' - Available in other lengths upon request.

ASTM & Code Standards

- Structural Framing is produced to meet or exceed ASTM C955
- Drywall Framing is produced to meet or exceed ASTM C645
- Galvanized sheet steel meets or exceeds requirements of ASTM A653 and ASTM A1003

Mill Steel Framing LEED Green Credits

MR Credit 2

ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable

MR Credit 4

• Recycled Content - Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content

MR Credit 5

· Regional Materials - Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas

V4 MR Credits • Building Product Disclosure and Optimization EPD (1 point)

· Materials Ingredients (1 point) - Construction and Demolition Waste Management (1 point)

