

www.millsteelframing.com | 2905 Lucerne Dr. SE Grand Rapids, MI 49546 | (812) 670-4195

Utility Angles

2X2ANGLE14GAG90

Product Description Coating

2" X 2" ANGLE 14 GAUGE G90 G90 *Also available in G90 coating

Physical Properties

| Design Thickness (in) | 0.0713 |
|------------------------|--------|
| Minimum Thickness (in) | 0.0677 |
| Leg 1 Length (in) | 2 |
| Leg 2 Length (in) | 2 |
| Yield Strength (ksi) | 33 |



Note

Standard stock length is 10' - Available in other lengths upon request.

ASTM & Code Standards

- Structural Framing is produced to meet or exceed ASTM C955
- Drywall Framing is produced to meet or exceed ASTM C645
- Galvanized sheet steel meets or exceeds requirements of ASTM A653 and ASTM A1003

Mill Steel Framing LEED Green Credits

| MR Credit 2 | ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable |
|---------------|---|
| MR Credit 4 | Recycled Content – Mill Steel Framing products contain no less than 25.5% post-consumer |
| | and 6.8% pre-consumer recycled content |
| MR Credit 5 | • Regional Materials – Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas |
| V4 MR Credits | Building Product Disclosure and Optimization EPD (1 point) |
| | • Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point) |

