

## Utility Angles

## 2X2ANGLE20GA

### Product Description

2" X 2" ANGLE 20 GAUGE

### Coating

G40

\*Also available in G90 coating

### Physical Properties

Design Thickness (in) 0.0312

Minimum Thickness (in) 0.0296

Leg 1 Length (in) 2

Leg 2 Length (in) 2

Yield Strength (ksi) 33



### Note

Standard stock length is 10' - Available in other lengths upon request.

### ASTM & Code Standards

- Structural Framing is produced to meet or exceed ASTM C955
- Drywall Framing is produced to meet or exceed ASTM C645
- Galvanized sheet steel meets or exceeds requirements of ASTM A653 and ASTM A1003

### Mill Steel Framing LEED Green Credits

- MR Credit 2** • ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable
- MR Credit 4** • Recycled Content – Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content
- MR Credit 5** • Regional Materials – Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas
- V4 MR Credits** • Building Product Disclosure and Optimization EPD (1 point)
- Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point)

