

www.millsteelframing.com | 2905 Lucerne Dr. SE Grand Rapids, MI 49546 | (812) 670-4195

Utility Angles 3X3ANGLE16GA

Product Description 3" X 3" ANGLE 16 GAUGE

Coating G60

*Also available in G90 coating

Physical Properties

Design Thickness (in) 0.0566
Minimum Thickness (in) 0.0538
Leg 1 Length (in) 3
Leg 2 Length (in) 3
Yield Strength (ksi) 33



Note

Standard stock length is 10' - Available in other lengths upon request.

ASTM & Code Standards

- Structural Framing is produced to meet or exceed ASTM C955
- Drywall Framing is produced to meet or exceed ASTM C645
- Galvanized sheet steel meets or exceeds requirements of ASTM A653 and ASTM A1003

Mill Steel Framing LEED Green Credits

MR Credit 2 MR Credit 4

- ConstructionWaste Management Mill Steel Framing steel framing is 100% recyclable
- Recycled Content Mill Steel Framing products contain no less than 25.5% post-consumer

and 6.8% pre-consumer recycled content

MR Credit 5
V4 MR Credit

• Regional Materials - Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas

V4 MR Credits • Building Product Disclosure and Optimization EPD (1 point)

• Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point)

