

www.millsteelframing.com | 2905 Lucerne Dr. SE Grand Rapids, MI 49546 | (812) 670-4195

Utility Angles

3X3ANGLE25GA

Product Description Coating

3" X 3" ANGLE 25 GAUGE G40 *Also available in G90 coating

Physical Properties

Design Thickness (in)	0.0188
Minimum Thickness (in)	0.0179
Leg 1 Length (in)	3
Leg 2 Length (in)	3
Yield Strength (ksi)	33



Note

Standard stock length is 10' - Available in other lengths upon request.

ASTM & Code Standards

- Structural Framing is produced to meet or exceed ASTM C955
- Drywall Framing is produced to meet or exceed ASTM C645
- Galvanized sheet steel meets or exceeds requirements of ASTM A653 and ASTM A1003

Mill Steel Framing LEED Green Credits

MR Credit 2	 ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable
MR Credit 4	• Recycled Content – Mill Steel Framing products contain no less than 25.5% post-consumer
	and 6.8% pre-consumer recycled content
MR Credit 5	• Regional Materials – Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas
V4 MR Credits	Building Product Disclosure and Optimization EPD (1 point)
	• Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point)

