

www.millsteelframing.com │ 2905 Lucerne Dr. SE Grand Rapids, MI 49546 │ (812) 670-4195

## **Z-FURRING** 150Z18GA

**Product Description** 1.50" Z-FURRING 18GA

Coating G40

**Physical Properties** 

Design Thickness (in) 0.0428 Height (in) 1.5 Leg 1 Length (in) 1.25 Leg 2 Length (in) 0.75 Yield Strength (ksi) 33



## **ASTM & Code Standards**

- AISI North American Specification (NASPEC) 2001 Supplement
- Furring channel is produced to meet or exceed ASTM C645
- Galvanized sheet metal meets or exceeds requirements of ASTM A924 & A1003

## Mill Steel Framing LEED Green Credits

MR Credit 2 MR Credit 4

• ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable

• Recycled Content - Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content

MR Credit 5

· Regional Materials - Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas

• Building Product Disclosure and Optimization EPD (1 point) V4 MR Credits

· Materials Ingredients (1 point) - Construction and Demolition Waste Management (1 point)

