

Z-FURRING

250Z18GA

Product Description
Coating

2.50" Z-FURRING18GA
G40

Physical Properties

| | |
|-----------------------|--------|
| Design Thickness (in) | 0.0428 |
| Height (in) | 2.5 |
| Leg 1 Length (in) | 1.25 |
| Leg 2 Length (in) | 0.75 |
| Yield Strength (ksi) | 33 |



ASTM & Code Standards

- AISI North American Specification (NASPEC) 2001 Supplement
- Furring channel is produced to meet or exceed ASTM C645
- Galvanized sheet metal meets or exceeds requirements of ASTM A924 & A1003

Mill Steel Framing LEED Green Credits

- | | |
|----------------------|--|
| MR Credit 2 | • ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable |
| MR Credit 4 | • Recycled Content – Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content |
| MR Credit 5 | • Regional Materials – Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas |
| V4 MR Credits | • Building Product Disclosure and Optimization EPD (1 point) • Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point) |

