

www.millsteelframing.com | 2905 Lucerne Dr. SE Grand Rapids, MI 49546 | (812) 670-4195

Z-FURRING 300Z18GA

Product Description 3.00" Z-FURRING 18GA

Coating G40

Physical Properties

Design Thickness (in) 0.0428
Height (in) 3
Leg 1 Length (in) 1.25
Leg 2 Length (in) 0.75
Yield Strength (ksi) 33



ASTM & Code Standards

- AISI North American Specification (NASPEC) 2001 Supplement
- Furring channel is produced to meet or exceed ASTM C645
- Galvanized sheet metal meets or exceeds requirements of ASTM A924 & A1003

Mill Steel Framing LEED Green Credits

MR Credit 2 MR Credit 4 • ConstructionWaste Management – Mill Steel Framing steel framing is 100% recyclable

WK Credit 4

 Recycled Content – Mill Steel Framing products contain no less than 25.5% post-consumer and 6.8% pre-consumer recycled content

MR Credit 5

• Regional Materials - Mill Steel Framing has manufacturing facilities in Indiana, Alabama & Texas

V4 MR Credits • Building Product Disclosure and Optimization EPD (1 point)

• Materials Ingredients (1 point) – Construction and Demolition Waste Management (1 point)

