

SECTION 1: IDENTIFICATION

Product Identifier

Product Name: Drago Mastic

Product Form: Water-based emulsion

Intended Use of the Product

Designed to be used as a vapor retardant membrane for use in conjunction with Drago® Wrap

Company Name, Address, and Telephone of the Responsible Party

Stego Industries, LLC

216 Avenida Fabricante #101 San Clemente, CA 92672 USA

Main Contact Number: (877) 464-7834

Emergency Telephone Number

Emergency Number: 1 (800) 424-9300 (24 Hrs.) CHEMTREC

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture Classification (GHS-US):

H225 – Flam. Lig. 2

H226 - Flam. Liq. 3

H304 – Asp. Tox. 1

H319 – Eye Irrit. 2A

H340 - Muta. 1B

H350 – Carc. 1B

H351 – Carc. 2

H400 – Aquatic Acute 1

H411 – Aquatic Chronic 2

Label Elements
GHS- US Labeling
Hazard Pictograms (GHS-US):









Signal Word (GHS-US): Danger **Hazard Statements (GHS-US):**

H225 – Highly flammable liquid and vapor.

H226 – Flammable liquid and vapor.

H304 - May be fatal if swallowed and enters airways.

H319 - Causes serious eye irritation.

H340 – May cause genetic defects by route of exposure if conclusively proven that no other route applies.

H350 – May cause cancer by route of exposure if conclusively proven that no other route applies.

H351 – Suspected of causing cancer by route of exposure if conclusively proven that no other route exposes.

H400 – Very toxic to aquatic life.

H411 - Toxic to aquatic life with long lasting effects.



SECTION 2: HAZARDS IDENTIFICATION Continued...

Precautionary Statements (GHS-US):

P201 – Obtain special instructions before use.

P202 – Do not handle until all safety precautions have been read and understood.

P210 – Keep away from heat.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 – Use explosion-proof electrical/ventilating/equipment.

P242 – Use only non-sparking tools.

P243 – Take precautionary measures against static discharge.

P264 - Wash face, hands, and any exposed skin thoroughly after handling.

P273 – Avoid release to the environment.

P280 – Wear protective gloves/protective clothing/eye protection/face protection.

P281 – Use personal protective equipment as required.

P303 + P361 + P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 – If exposed or concerned: Get medical advice/attention.

P337 + P313 – If eye irritation persists: Get medical attention/advice.

P370 + P378 – In case of fire: Use extinguishing media for extinction.

P391 – Collect spillage.

P 403 + P235 - Store in a well-ventilated place. Keep cool.

P405 – Store lock up.

P501- Dispose of contents/container according to local, regional, national, and international regulations.

Other Hazards

Other Hazards Not Contributing to the Classification: Not available.

Unknown Acute Toxicity (GHS-US)

No data available.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Substance

Not available.

Mixture

Name	CAS Number	% by WT	Classification (GHS-US)		
Asphaltic Cement	8052-42-4	50 – 65%	H225 – Flam. Liq. 2		
			H319 – Eye Irrit. 2A		
			H351 – Carc. 2		
Water	7732-18-5	20 – 45%	Not Classified		
Elastomeric Polymer	Proprietary	0 – 20%	Not Classified		
Additives	Mixture	0 - 6%	Not Classified		
Stoddard	8052-41-3	0 – 5%	H226 – Flam. Liq. 3		
			H304 – Asp. Tox. 1		
			H340 – Muta. 1B		
			H350 – Carc. 1B		
			H400 – Aquatic Acute 1		
			H411 – Aquatic Chronic 2		



SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

First-Aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). IF exposed or concerned: Get medical advice/attention.

First-Aid Measures After Inhalation: Move to fresh air. Oxygen or artificial respiration if needed. If symptoms persist, call a physician.

First-Aid Measures After Skin Contact: Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. Remove and wash contaminated clothing before re-use. If skin irritation persists, call a physician. **First-Aid Measures After Eye Contact:** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

First-Aid Measures After Ingestion: Call a physician or Poison Control Center immediately. Never give anything by mouth to an unconscious person. Do not induce vomiting without medical advice.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Carbon dioxide (CO2). Foam. Dry powder. Dry chemical.

Unsuitable Extinguishing Media: Do not use a solid water stream as it may scatter and spread fire.

Special Hazards Arising From the Substance or Mixture

No information available.

Advice for Firefighters

Fire-Fighting Instructions: Exercise caution when fighting any chemical fire.

Protection During Fire-Fighting: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/ NIOSH (approved or equivalent) and full protective gear.

Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Evacuate personnel to safe areas.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.



SECTION 6: ACCIDENTAL RELEASE MEASURES Continued...

Methods and Material for Containment and Cleaning Up

For Containment and Clean Up: Dike with inert absorbent material (e.g. dry sand or earth). Take precautionary measures against static discharges. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Keep in suitable and closed containers for disposal. Dispose of as common waste.

Reference to Other Sections

See Section 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Avoid contact with skin and eyes. Ensure adequate ventilation.

Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Keep container tightly closed. Keep in properly labeled containers. Keep out of the reach of children. Store at room temperature.

Incompatible Materials: Not available.

Installation Temperature Range: 40-130°F (surface)

In-Service Temperature Range: 10-130°F (surface and surrounding)

Exposure to Ultraviolet Radiation/Weather Events: The amount of time between when Drago Mastic is installed and when concrete is placed or other complete protection from sunlight and weather events is provided should be minimized while not exceeding 7 days.

Please review the remainder of the SDS and relevant technical data sheets for storage and additional information. If any of the conditions cited above pose a problem for the typical installation of the Drago Mastic, please contact Stego Industries for additional information and solutions.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters

Chemical Name	ACGIH TLV	OSHA PEL	Ontario TWAEV	Mexico
Petroleum Asphalt	TWA: 0.5 mg/m ³		TWA: 0.5 mg/m ³	STEL: 10 mg/m ³
				TWA: 5 mg/ m ³
Stoddard Solvent	TWA: 100 ppm	TWA: 2900 mg/m ³	TWA: 525 mg/m ³	STEL: 200 ppm
		TWA: 500 ppm		STEL: 1050 mg/ m ³
				TWA: 523 mg/ m ³
				TWA: 100 ppm

Chemical Name	NIOSH IDLH		
Stoddard Solvent	20,000 mg/m ³		

Exposure Controls

Appropriate Engineering Controls: Do not allow ventilation equipment to draw material odors indoors. **Personal Protective Equipment:** Gloves. Protective clothing. Protective goggles.





Continued...

Note - legal notice on page 8



SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION Continued...

Hand Protection: Protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protec-

tion should be worn.

Hygiene Measure: Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before

re-use. Handle in accordance with good industrial hygiene and safety practice.

Other Information: When using, do not eat, drink, or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical Sate Liquid

Appearance Brown/black liquid

OdorSlight OdorOdor ThresholdNot AvailablepH9.5-11.5

Relative Evaporation Rate (butyl acetate = 1) Not Available **Melting Point** Not Available **Freezing Point** 32°F / 20°C **Boiling Point** 212°F / 100°C Flash Point >400°F / 204°C **Auto-ignition Temperature** >700°F / >371°C **Decomposition Temperature** Not Available Not Available Flammability (solid, gas) Lower Flammability Limit Not Available Not Available **Upper Flammability Limit** Not Available **Vapor Pressure**

Vapor PressureNot AvailableRelative Vapor Density at 68°F (20°C)>1 (air = 1)Relative DensityNot Available

Specific Gravity >1.0

SolubilityPartly misciblePartition Coefficient: n-octanol/waterNot AvailableExplosion Data - Sensitivity to Mechanical ImpactNot AvailableExplosion Data - Sensitivity to Static DischargeNot AvailableVOC Content<16 g/L</th>

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous polymerization does not occur. **Chemical Stability:** Stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Contact with strong oxidizing agents may create gelling and water condensation.

Incompatible Materials: No materials to be especially mentioned.

Hazardous Decomposition Products: Carbon monoxide. Carbon dioxide. Hydrocarbons.



SECTION 11: TOXICOLOGICAL INFORMATION Continued...

Information on Toxicological Effects - Ingredient(s) LD50 and LC50 Data:

Asphalt (8052-42-4)	
LD50 Oral Rat	>5,000 mg/kg
LD50 Dermal Rabbit	>2,000 mg/kg

Carcinogenicity Data:

Asphalt (8052-42-4)	
IARC Group	2B
National Toxicity Program (NTP) Status	Twelfth Report – Items under consideration

SECTION 12: ECOLOGICAL INFORMATION

Toxicity - Ingredients

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Persistence and Degradability

No information available for this product.

Bioaccumulative Potential - Product

No information available for this product.

Bioaccumulative Potential - Ingredients

No information available for this product.

Mobility in Soil

No information available for this product.

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of in accordance with local, state, and federal regulations. Additional Information: Empty containers should be taken for local recycling, recovery or waste disposal.

Non-Regulated Material

SECTION 14: TRANSPORT INFORMATION

In Accordance with DOT

Proper Shipping Name Non-Regulated Material

In Accordance with IMDG

Proper Shipping Name

Hazard Class

Identification Number

Packing Group

Marine Pollutant

Continued...

Note - legal notice on page 8



SECTION 14: TRANSPORT INFORMATION Continued...

In Accordance with IATA

Proper Shipping Name

Non-Regulated Material

Hazard Class

Identification Number

Packing Group
Marine Pollutant

In Accordance with TDG

Proper Shipping Name

Non-Regulated Material.

Hazard Class

Identification Number

Packing Group

Marine Pollutant

SECTION 15: REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL	NDSL	EINECS	ELINCS	ENCS	CHINA	KECL	PICCS	AICS
Petroleum Asphalt	Χ	X		X			Χ	Χ	Χ	Χ
Stoddard Solvent	Χ	Х	Х	X	Χ	Χ	Χ	Х	Χ	Х

TSCA: Complies DSI -Complies NIDSL: Complies **EINECS:** Complies **ELINCS:** Complies **ENCS:** Complies CHINA: Complies KECL: Complies PICCS: Complies AICS: Complies

US Federal Regulation

Asphalt (8052-42-4): Listed on the United States Toxic Substances Control Act (TSCA) Inventory. **Elastomeric Polymer (Proprietary):** Listed on the United States Toxic Substances Control Act (TSCA) Inventory.

California Proposition 65: This product contains no known Proposition 65 chemicals.

State-Right-to-Know

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Petroleum Asphalt	X	X	X		X
Stoddard Solvent	X	X	Χ		X

Canada Regulations

All components are listed in the WHMIS DSL.

WHMIS Classification: Not classified.



SECTION 16: OTHER INFORMATION

Other Information: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Disclaimer: The information contained herein only applies to the noted product. To the best of our knowledge, having been obtained through our suppliers or third parties, this information is accurate. We make no warranties, express or implied, concerning this information or the safe use of the noted product, and we disclaim liability from loss, damage, or other from the product's use, handling, or storage. Users are responsible for verifying the fitness/suitable of the product for any purposes/applications and for confirming compliance with any/all relevant codes or regulations.

Please read the Product Statements for all Drago® products by navigating here: stegoindustries.com/legal