



Revision Date: May 18, 2021 | Date of Issue: June 1, 2017 | Version Number: 6.0

## SECTION 1: IDENTIFICATION

### Product Identifier

**Product Name:** Drago Tape

### Intended Use of the Product

Accessory of Drago® Wrap Vapor Intrusion Barriers; used to seal penetrations in Drago Wrap.

### Company Name, Address, and Telephone of the Responsible Party

Stego Industries, LLC

216 Avenida Fabricante #101

San Clemente, CA 92672 USA

**Main Contact Number:** (877) 464-7834

### Emergency Telephone Number

**Emergency Number:** 1 (800) 424-9300 (24 Hrs.) CHEMTREC

## SECTION 2: HAZARDS IDENTIFICATION

**Classification:** This product is not classified as hazardous in accordance with 29 C.F.R. § 1910.1200.

**Signal word:** None.

**Pictogram(s):** None.

**Hazard statement(s):** None.

**Precautionary statement(s):** None.

**Hazards not otherwise classified:** Polymer film can burn if exposed to excessive temperatures beyond the normal use of the product.

## SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS Number	% by WT.
Modified Acrylic Adhesive	Proprietary*	10-25%*
Release Coated Polymeric Film	Mixture	75-90%

The selections marked with an '\*' are proprietary and considered to be Trade Secrets. This is the reason that they are listed as such, or provided as a range.

## SECTION 4: FIRST AID MEASURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Inhalation:** Not a respirable film. If exposed to fumes from combustion, move subject to fresh air; if breathing is difficult, give oxygen and get medical attention; if victim has stopped breathing, give artificial respiration and get medical attention.

**Eye Contact:** Not a probable route of exposure. If exposed to fumes from overheating or from combustion, move subject to fresh air. Flush with plenty of water; if irritation continues, get medical attention.

**Skin Contact:** No treatment necessary. For thermal burns, cool molten materials with water and get medical attention.

**Ingestion:** Not a probable route of exposure.

*Continued...*

*Note - legal notice on page 5*



Revision Date: May 18, 2021 | Date of Issue: June 1, 2017 | Version Number: 6.0

## SECTION 5: FIRE-FIGHTING MEASURES

**Unusual Hazards:** Polymer film can burn if exposed to excessive temperature beyond the normal use of the product.

**Extinguishing Agents:** Use extinguishing media appropriate for surrounding fire: carbon dioxide, foam, dry chemical, and water fog. Use fire extinguishers with class A extinguishing agents (e.g., water, foam)

**Personal Protective:** Equipment unnecessary unless resin is burned, which is not an intended use of the product. If resin is burning, wear self-contained breathing apparatus (pressure-demand MSHA/NIOSH approved or equivalent) and full protective gear.

**Special Fire Fighting Procedures:** Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Note:** See Section 10 for hazardous combustion and thermal decomposition information.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**Personal Protection:** None necessary.

**Procedures (Clean-up Methods, Environmental Precautions):** None necessary.

## SECTION 7: HANDLING AND STORAGE

**Storage Conditions:** Cool, dry storage recommended. Indoor storage recommended.

Avoid storing films in areas containing aromatic hydrocarbons, halogenated compounds, chlorinated compounds, oxidative agents, solvents or other known polyethylene solubilizers, prodegradants, as they may impact the product performance and/or service life.

**Handling Procedures:** Avoid direct sunlight. Avoiding direct UV exposure of product. Avoid contact with incompatible materials.

Installation Temperature Range: 5-100°F (surface and ambient).

In-Service Temperature Range: -20-160°F (surface and surrounding).

Exposure to Ultraviolet Radiation/Weather Events: The amount of time between when Drago Tape is installed and when concrete is placed or other complete protection from sunlight and weather events is provided should be minimized while not exceeding 7 days.

Please review the remainder of the SDS and relevant technical data sheets for storage and additional information. If any of the conditions cited above pose a problem for the typical installation of the Drago Tape, please contact Stego Industries for additional information and solutions.

## SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

**Respiratory Protection:** None required during handling. Local exhaust to remove fumes from heat sealing and hot wire cutting areas of packaging or bag converting for worker comfort.

**Eye/Face Protection:** None necessary under normal use.

**Hand/Skin Protection :** None necessary under normal use.

**Engineering Controls (Ventilation):** Use local exhaust ventilation when routinely heat sealing this product.

Recommended ventilation is with a minimum capture velocity of 100 ft/min. (30 m/min.) at the point of vapor evolution. Refer to the current edition of *Industrial Ventilation: A Manual of Recommended Practice* published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

**Other Protective Equipment:** None necessary under normal use.

*Continued...*

*Note - legal notice on page 5*



Revision Date: May 18, 2021 | Date of Issue: June 1, 2017 | Version Number: 6.0

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES** *Continued...*

**General Physical Form:** Modified acrylic adhesive adhesive coated onto a modified polyolefin film.

**INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance</b>	Single-sided tape
<b>Color</b>	Gray
<b>State</b>	Solid
<b>Odor Characteristics</b>	None
<b>Odor Threshold</b>	None
<b>pH</b>	Not Applicable
<b>Melting Point/Freezing Point</b>	Not Applicable
<b>Initial Boiling Point and Boiling Point Range</b>	Not Applicable
<b>Flash Point</b>	Not Applicable
<b>Evaporation Rate</b>	Not Applicable
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Upper flammability</b>	Not Applicable
<b>Lower Flammability</b>	Not Applicable
<b>Vapor Pressure</b>	Not Applicable
<b>Vapor Density</b>	Not Applicable
<b>Relative Density</b>	Not Applicable
<b>Solubility in water</b>	Not Applicable
<b>Partition Coefficient: n-octanol/water</b>	Not Applicable
<b>Auto ignition-temperature</b>	Not Applicable
<b>Decomposition temperature</b>	>325°C (617°F)
<b>Viscosity</b>	Not Applicable
<b>Volatile Organic Compounds</b>	No Data Available
<b>Percent Volatile</b>	Not Applicable
<b>VOC less H2O and Exempt Solvents</b>	No Data Available

**SECTION 10: STABILITY AND REACTIVITY**

**Instability:** This material is considered stable. However, temperatures above 325°C, is the onset of polymer decomposition. Thermal decomposition is dependent on time and temperature.

**Hazardous Decomposition Products**

Substance	Condition
Hydrocarbons	Combustion by-product
Carbon Monoxide	Combustion by-product
Carbon Dioxide	Combustion by-product

**Hazardous Polymerization:** Product will not undergo hazardous polymerization. Product does not decompose at ambient temperatures.

**Hazardous Decomposition:** Under recommended usage conditions, hazardous decomposition products are not expected. Hazardous decomposition products may occur as a result of oxidation, heating, or reaction with another material.

*Continued...*

*Note - legal notice on page 5*



Revision Date: May 18, 2021 | Date of Issue: June 1, 2017 | Version Number: 6.0

## SECTION 11: TOXICOLOGICAL INFORMATION

This product, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. However, use or processing of the product in a manner not in accordance with the product's directions for use may affect the performance of the product and may present potential health and safety hazards.

**Acute Data:** No Toxicity data are available for this material.

### PRIMARY ROUTES OF EXPOSURE

**Skin Contact:** Only if burned.

**Eye Contact:** Only if burned.

**Respiratory Contact:** Only if burned.

### ACUTE EFFECTS OF EXPOSURE

**Ingestion:** Not a probable route of exposure.

**Inhalation:** No inhalation risk unless product is heated to point of burning, which in normal applications does not occur. Fumes from combustion are unlikely to be produced during heat shrinking. Local ventilation should be used for comfort.

**Eye Contact:** No eye exposure risk during all product usage except during heating if plastic is heated to point of combustion, which does not occur during the intended use of the product. Fumes from combustion, which have a low toxicity, may be produced during hot wire cutting or heat sealing. Fumes are unlikely to be produced during heat shrinking when used as directed.

**Skin Contact:** Not irritating when used as directed. Hot polymer created during heat shrinking, wire cutting, or heat sealing, may produce thermal burns.

**Chronic Effects of Exposure:** None known when used as directed.

**Carcinogenicity:** None known when used as directed.

## SECTION 12: ECOLOGICAL INFORMATION

This material is insoluble in water and not expected to present any environmental problems in normal application, however areas containing aromatic hydrocarbons, halogenated compounds, chlorinated compounds, pH extremities, oxidative agents, solvents or other known polyethylene solubilizers, prodegradants, etc. may impact the product performance and/or service life.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Procedure:** Reclaim if feasible. If product can't be reclaimed, no special requirements are necessary; dispose of as ordinary solid waste. Pick up film for good "housekeeping" and to prevent a slipping hazard. Incineration or landfill in compliance with federal, state and local regulations. *Since regulations vary, consult applicable regulations or authorities before disposal.*

## SECTION 14: TRANSPORT INFORMATION

**US DOT Hazard Class:** Not regulated.

## SECTION 15: REGULATORY INFORMATION

**Workplace Classification:** This product is not considered hazardous under the OSHA Hazard Communication Standard (29 C.F.R. § 1910.1200).

**Waste Classification:** When this product becomes a waste, it is classified as a non-hazardous waste under criteria of the Resource Conservation and Recovery Act (40 C.F.R. 261).

*Continued...*

*Note - legal notice on page 5*



Revision Date: May 18, 2021 | Date of Issue: June 1, 2017 | Version Number: 6.0

## SECTION 16: OTHER INFORMATION

### NFPA HAZARD RATING

Health: 0 | Flammability: 1 | Reactivity: 0 | Special Hazards: None

*Scale: 4 = Extreme | 3 = High | 2 = Moderate | 1 = Slight | 0 = Insignificant*

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material, but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

*Rating are based on internal supplier's guidelines, and they are intended for internal use only.*

### ABBREVIATIONS:

ACGIH = American Conference of Governmental Industrial Hygienists

OSHA = Occupational Safety and Health Administration

TLV = Threshold Limit Value

PEL = Permissible Exposure Limit

TWA = Time Weighted Average

STEL = Short-Term Exposure Limit

**Disclaimer:** The information contained herein only applies to the noted product. To the best of our knowledge, having been obtained through our suppliers or third parties, this information is accurate. We make no warranties, express or implied, concerning this information or the safe use of the noted product, and we disclaim liability from loss, damage, or other from the product's use, handling, or storage. Users are responsible for verifying the fitness/suitable of the product for any purposes/applications and for confirming compliance with any/all relevant codes or regulations.

Please read the Product Statements for all Drago® products by navigating here: [stegoindustries.com/legal](https://stegoindustries.com/legal)