



# DRAGOTACK® TAPE

A STEGO INDUSTRIES, LLC INNOVATION | VAPOR RETARDERS 07 26 00, 03 30 00 | VERSION: JUNE 7, 2021

## 1. PRODUCT NAME

**DRAGOTACK TAPE**

## 2. MANUFACTURER

Stego® Industries, LLC  
 216 Avenida Fabricante, Suite 101  
 San Clemente, CA 92672  
 Sales, Technical Assistance  
 Ph: (877) 464-7834  
 contact@stegoindustries.com  
 stegoindustries.com



## 3. PRODUCT DESCRIPTION

**USES:** Dragotack Tape is a solvent-resistant, double-sided adhesive strip used to bond and seal Drago® Wrap to concrete, masonry, wood, metal, and other surfaces. Dragotack Tape is a flexible and moldable material to allow for a variety of applications and installations.

**COMPOSITION:** Dragotack Tape is made from a solvent-resistant blend of synthetic rubber and resins.

**SIZE:** Dragotack Tape is 2" x 50'. Dragotack Tape ships 12 rolls in a case.

## 4. TECHNICAL DATA

**TABLE 4.1: PHYSICAL PROPERTIES OF DRAGOTACK TAPE**

PROPERTY	TEST	RESULTS
Dimensions		2" x 50'
Total Thickness		30 mil
Color		Grey
Material		Synthetic rubber blend
Permeance	ASTM F1249	0.03 perms (30 mil)
Adhesion to Steel	ASTM D1000	12.5 lbs/in width
Chemical Resistance (TCE, PCE, Toluene, Xylene)	ASTM D471 / D543	No significant change to mass or volume.
Installation Temperature		40°F / 110°
In Service Temperature Range		-20°F / +140°F
VOC Content		No VOCs, 100% solids

Note: perm unit = grains/(ft<sup>2</sup>\*hr\*in-Hg)

Continued...

Note – legal notice on page 2.

## DRAGOTACK® TAPE

A STEGO INDUSTRIES, LLC INNOVATION | VAPOR RETARDERS 07 26 00, 03 30 00 | VERSION: JUNE 7, 2021

### 5. INSTALLATION

**TO WALLS AND FOOTINGS:** Make sure the area of adhesion is free of dust, dirt, debris, moisture, and frost to allow maximum adhesion. Remove release liner on one side and stick to desired surface. When ready to apply Drago Wrap, remove the exposed release liner and press Drago Wrap firmly against DragoTack Tape to secure.

Cut DragoTack Tape using a utility knife or scissors. Cut DragoTack Tape before removing the release liner for easier cutting. Install DragoTack Tape between 40°F and 110°F.

Review Drago Wrap's complete installation instructions prior to installation.

### 6. AVAILABILITY & COST

DragoTack Tape is available nationally through our network of building supply distributors. For current cost information, contact your local Drago distributor or Stego Industries' Sales Representative.

### 7. WARRANTY

Stego Industries, LLC believes to the best of its knowledge, that specifications and recommendations herein are accurate and reliable. However, since site conditions are not within its control, Stego Industries does not guarantee results from the use of the information provided herein. Stego Industries, LLC does offer a limited warranty on Drago Wrap. Please see [stegoindustries.com/legal](https://stegoindustries.com/legal)

### 8. MAINTENANCE

Store DragoTack Tape in a dry and temperate area.

### 9. TECHNICAL SERVICES

Technical advice, custom CAD drawings, and additional information can be obtained by contacting Stego Industries or by visiting the website.

**Email:** [contact@stegoindustries.com](mailto:contact@stegoindustries.com)

**Contact Number:** (877) 464-7834

**Website:** [stegoindustries.com](https://stegoindustries.com)

### 10. FILING SYSTEMS: [stegoindustries.com](https://stegoindustries.com)

(877) 464-7834 | [stegoindustries.com](https://stegoindustries.com)

DATA SHEETS ARE SUBJECT TO CHANGE. FOR MOST CURRENT VERSION, VISIT [STEGOINDUSTRIES.COM](https://stegoindustries.com)

