



# STEGOTACK® TAPE

A STEGO INDUSTRIES, LLC INNOVATION | VAPOR RETARDERS 07 26 00, 03 30 00 | VERSION: MAY 26, 2021

## 1. PRODUCT NAME

STEGOTACK TAPE

## 2. MANUFACTURER

Stego® Industries, LLC  
 216 Avenida Fabricante, Suite 101  
 San Clemente, CA 92672  
 Sales, Technical Assistance  
 Ph: (877) 464-7834  
 contact@stegoindustries.com  
 stegoindustries.com



## 3. PRODUCT DESCRIPTION

**USES:** StegoTack Tape is a double-sided adhesive strip used to bond and seal the Stego below-slab and crawl space water vapor barriers or retarders to concrete, masonry, wood, metal, and other surfaces.

**COMPOSITION:** StegoTack Tape is made from a blend of synthetic rubber and resins.

**SIZE:** StegoTack Tape is 2" x 50'. StegoTack Tape ships 12 rolls in a case.

### FEATURES AND BENEFITS:

- Highly flexible and moldable
- Low VOC Emissions - Certified Clean Air GOLD
- Made in the USA



The versatility of StegoTack Tape makes it an excellent option for Stego Wrap, StegoHome, and StegoCrawl installation applications.

## 4. TECHNICAL DATA

**TABLE 4.1: PHYSICAL PROPERTIES OF STEGOTACK TAPE**

PROPERTY	RESULTS
Dimensions	2" x 50'
Total Thickness	30 mil
Permeance (30 mil)	0.03 perms
Color	Grey
Material	Synthetic rubber blend
Adhesion to Steel	12.5 lb/in width ASTM D1000
Installation Temperature	40°F/110°F
In Service Temperature Range	-20°F/+140°F
VOC Content	No VOCs, 100% solids

Note: perm unit = grains/(ft<sup>2</sup>\*hr\*in-Hg)

Continued...

Note – legal notice on page 2.

## STEGOTACK® TAPE

A STEGO INDUSTRIES, LLC INNOVATION | VAPOR RETARDERS 07 26 00, 03 30 00 | VERSION: MAY 26, 2021

### 5. INSTALLATION

**TO WALLS:** Make sure the area of adhesion is free of dust, dirt, debris, moisture, and frost to allow maximum adhesion. Remove release liner on one side and stick to desired surface. When ready to apply the vapor barrier or retarder, remove the exposed release liner and press the vapor barrier or retarder firmly against StegoTack Tape to secure.

Cut StegoTack Tape using a utility knife or scissors. Cut StegoTack Tape before removing the release liner for easier cutting. Install StegoTack Tape between 40°F and 110°F. For additional information please refer to Stego's complete installation instructions.

### 6. AVAILABILITY & COST

StegoTack Tape is available through our network of building supply distributors. For current cost information, contact your local Stego distributor or Stego Industries' Sales Representative.

### 7. WARRANTY

Stego Industries, LLC believes to the best of its knowledge, that specifications and recommendations herein are accurate and reliable. However, since site conditions are not within its control, Stego Industries does not guarantee results from the use of the information provided herein. Stego Industries, LLC does offer a limited warranty on Stego Wrap. Please see [stegoindustries.com/legal](http://stegoindustries.com/legal)

### 8. MAINTENANCE

For longer adhesive life, store in dry, temperate area.

### 9. TECHNICAL SERVICES

Technical advice, custom CAD drawings, and additional information can be obtained by contacting Stego Industries or by visiting the website.

**Email:** [contact@stegoindustries.com](mailto:contact@stegoindustries.com)

**Contact Number:** (877) 464-7834

**Website:** [stegoindustries.com](http://stegoindustries.com)

### 10. FILING SYSTEMS: [stegoindustries.com](http://stegoindustries.com)



(877) 464-7834 | [stegoindustries.com](http://stegoindustries.com)

DATA SHEETS ARE SUBJECT TO CHANGE. FOR MOST CURRENT VERSION, VISIT: [STEGOINDUSTRIES.COM](http://STEGOINDUSTRIES.COM)