





Interior Finish Products




- Versatility of Spray
- Caulk and Spray Compatibility
- Dynamic Movement
- Penetrants in Head-of-Wall Joints
- CPVC Compatibility with Spray

We offer flexible joint sealants and sprays or gasket materials that allow for dynamic movement. All of our systems are fully tested according to ANSI/UL2079, ASTM E1966, ASTM E1399, ULC-S115, EN 1366-4, and other relevant standards relating to movement and fire testing of joint systems.

We understand the nuances of firestopping

head-of-wall joints and other joint systems





Elastomeric Spray

SpecSeal® AS200 Elastomeric Spray is a latexbased elastomeric firestop spray for construction joints and perimeter fire barrier applications. AS200 cures to form a durable seal that resists the passage of the products of combustion while accommodating for high dynamic joint movement.



SEP

SpeedFlex® Joint Profile System

SpeedFlex® Joint Profile partners with SpecSeal® spray-applied coatings to provide unsurpassed joint movement capabilities in standard gypsum board construction. SpeedFlex® Joint Profile eliminates the need for traditional forming materials allowing for reduced application times increasing productivity.



Elastomeric Firestop Sealant

SpecSeal® ES Sealant is a latex-based gun grade elastomeric firestop sealant designed for construction joint applications. Once cured, ES Sealant forms a flexible shield against the passage of fire and smoke. In dynamic joint conditions, ES Sealant is tested to accommodate up to 25% compression/extension of the installed joint width.



speedFlex® TTG Track Top Gasket makes short work of construction joints in gypsum board construction. TTG eliminates the need for firestop sealants or sprays by firestopping as the wall is constructed. Track Top Gasket is easily cut to length with scissors or a sharp knife, installing quick with no waste. Custom sizes available upon request.



Endothermic Sealant

SpecSeal® LC Endothermic Sealant is a latex-based gun grade firestop sealant for construction joints and non-combustible penetrations. After application, LC Sealant cures to form a flexible seal against the propagation of fire. Under fire exposure, LC absorbs heat and release water vapor resisting the progress of smoke and flame.



Smoke'N'Sound Acoustical Spray

SpecSeal® Smoke 'N' Sound spray is a high quality acrylic latex spray designed for static or minimally dynamic linear joints or gaps. Formulated to adhere to all common construction surfaces and can be applied using airless spray equipment or with a brush (for small applications and touch ups).



Smoke'N'Sound Acoustical Sealant

A high quality acrylic latex sealant designed for sealing through-penetrations (such as pipes, conduits, cabling, busways, and openings) and membrane penetrations (such as p-traps and outlet boxes) in smoke resistant walls.



		ORDERING INFORMATION	ON		
Catalog Number	UPC Number	Description	(UOM) Qty.	Case Qty.	Weight (Each)
AS205	730573071076	Elastomeric Spray 5 Gallon Pail	1	1	53.60 lbs (24.31 kg)liters)
AS205R	730573071083	Elastomeric Spray 5 Gallon Pail (Red)	1	1	53.60 lbs (24.31 kg)

SpecSeal® SpeedFlex® Joint Profile

ORDERING INFORMATION							
Catalog Number	UPC Number	Description	(UOM) Qty.	Case Qty.	Weight (Each)		
SFJP40	730573081440	Joint Profile	1	150 per box	0.21 lbs (0.10 kg)		
SFJP80	730573081457	Joint Profile for Wider Joints	1	75 per box	0.42 lbs (0.19 kg)		

SpecSeal® Series ES Elastomeric Sealant

		ORDERING INFORMATION			
Catalog Number	UPC Number	Description	(UOM) Qty.	Case Qty.	Weight (Each)
ES100	730573081006	10.1 oz. Tube (300 ml) 18.2 cu.in.	1	12	1.08 lbs (0.49 kg)
ES100R	730573081013	10.1 oz. Tube (300 ml) 18.2 cu.in Red	1	12	1.08 lbs (0.49 kg)
ES105	730573081051	5 Gal. Pail (19.0 liters) 1,155 cu.in.	1	N/A	63.30 lbs (28.71 kg)
ES105R	730573081068	5 Gal. Pail (19.0 liters) 1,155 cu.in Red	1	N/A	63.30 lbs (28.71 kg)
ES120	730573081037	20 oz. Sausage (592 ml) 36 cu. in.	1	12	1.97 lbs (0.89 kg)
ES120R	730573081044	20 oz. Sausage (592 ml) 36 cu. in Red	1	12	1.97 lbs (0.89 kg)
ES129	730573081297	29 oz. Tube (858 ml) 52 cu. in.	1	10	3.05 lbs (1.38 kg)
ES129R	730573081310	29 oz. Tube (858 ml) 52 cu. in Red	1	10	3.05 lbs (1.38 kg)

SpeedFlex® Track Top Gasket

ORDERING INFORMATION									
Catalog Number	UPC Number	Description	(UOM) Qty.	Case Qty.	Weight (Each)	Width			
TTG250J	730573082508	Gasket for 2.5" (63.5 mm) J-Runners - 150' (45.7 meter) roll	1	1	16.57 lbs (7.52 kg)	6.25" (159 mm)			
TTG350F	730573083550	Gasket with folded legs for 3-1/2" (89 mm) or 3-5/8" (92 mm) ceiling track - 2' x 80.5' (24.5 meter) rolls	1	1	16.58 lbs (7.52 kg)	6.25" (159 mm)			
TTG400J	730573084007	Gasket for 4" (102 mm) J-Runners - 150' (45.7 meter) roll	1	1	18.62 lbs (8.45 kg)	7.50" (191 mm)			
TTG600F	730573086049	Gasket with folded legs for6" (152 mm) ceiling track - 2' x 80.5'(24.5 meter) rolls	1	1	23.47 lbs (10.65 kg)	8.63" (219 mm)			
TTG600J	730573086025	Track Top Gasket for 6" (152 mm) J-Runners - 150' (45.7 meter) roll	1	1	23.64 lbs (10.72 kg)	9.7" (248 mm)			

SpecSeal® LC Endothermic Firestop Sealant

ORDERING INFORMATION							
UPC Number	Description	(UOM) Qty.	Case Qty.	Weight (Each)			
730573011300	Endothermic Firestop Sealant 10.1 oz Tube	1	12	0.96 lbs (0.44 kg)			
730573011331	Endothermic Firestop Sealant 20 oz. Sausage	1	12	1.70 lbs (0.77 kg)			
730573011317	Endothermic Firestop Sealant 29 oz. Tube	1	12	2.56 lbs (1.16 kg)			
730573011355	Endothermic Firestop Sealant 5 gal. Pail	1	1	55.81 lbs (25.31 kg)			
	730573011300 730573011331 730573011317	UPC NumberDescription730573011300Endothermic Firestop Sealant 10.1 oz Tube730573011331Endothermic Firestop Sealant 20 oz. Sausage730573011317Endothermic Firestop Sealant 29 oz. Tube	UPC NumberDescription(UOM) Qty.730573011300Endothermic Firestop Sealant 10.1 oz Tube1730573011331Endothermic Firestop Sealant 20 oz. Sausage1730573011317Endothermic Firestop Sealant 29 oz. Tube1	UPC NumberDescription(UOM) Qty.Case Qty.730573011300Endothermic Firestop Sealant 10.1 oz Tube112730573011331Endothermic Firestop Sealant 20 oz. Sausage112730573011317Endothermic Firestop Sealant 29 oz. Tube112			

SpecSeal® Smoke 'N' Sound Smoke and Acoustical Sealant & Spray

ORDERING INFORMATION							
Catalog Number	UPC Number	Description	(UOM) Qty.	Case Qty.	Weight (Each)		
SNS105W	730573111543	Smoke & Acoustical Sealant, 5 Gallon Pail	1	1	70.06 lbs (31.78 kg)		
SNS120W	730573111512	Smoke & Acoustical Sealant, 20 oz. (592 ml) Sausage	1	12	2.11 lbs (0.96 kg)		
SNS129W	730573111529	Smoke & Acoustical Sealant, 29 oz. (858 ml) Tube	1	12	3.29 lbs (1.49 kg)		
SNS205	730573011553	Smoke & Acoustical Spray, 5 Gallon Pail	1	1	55.48 lbs (25.17 kg)		





For more information visit www.stifirestop.com/cw or contact your local sales representative at 800-992-1180.