

SpecSeal[®]
SIL

HIGH PERFORMANCE SILICONE FIRESTOP SEALANT

SIL300 Silicone Firestop Sealant

SpecSeal[®] SIL300 Silicone Firestop Sealant is a silicone firestop sealant tested to resist the passage of flames, smoke, hot gases, and water in construction joints and penetration firestop systems. SIL300 Sealant cures to form a flexible seal and carries a Class 1 W Rating for water tightness (Per ANSI/UL1479).

Features & Benefits

- Available in a Gun Grade or Self Leveling
- Ozone and UV Resistant
- Excellent recovery from joint extension and compression
- Listed in over 175 UL[®] Tested Systems
- Excellent chemical resistance




ORDERING INFORMATION

Catalog Number	UPC Number	Size	(UOM) Qty.	Case Qty.	Weight (Each)
SIL300	730573013106	10.1 oz Tube (300 ml) 18.2 cu. in.	1	24	1.03 lbs (0.47 kg)
SIL305	730573013052	4.5 Gal. Pail (17.0 liters) 1,037 cu. in.	1	1	54.43 lbs (24.69 kg)
SIL320	730573013205	20 oz. Sausage Tube (592 ml) 36 cu. in.	1	12	1.86 lbs (0.84 kg)
SIL305SL	730573013267	Self-leveling 4.5 Gal. Pail (17.0 liters) 1,037 cu. in.	1	1	51.89 lbs (23.54 kg)
SIL320SL	730573013229	Self-leveling 20 oz. Sausage Tube (592 ml) 36 cu. in.	1	12	1.86 lbs (0.84 kg)



TEST STANDARDS: ASTM E814 (UL 1479), ASTM E1966 (UL 2079), CAN/ULC-S115

SIL300 Color: Concrete (Limestone)
SIL300SL Color: Gray



Specified Technologies Inc.
Firestop, Smoke, & Sound Solutions

Click or scan to learn more



ZST13532 25343