



LIGHT-WEIGHT, COST EFFECTIVE SOLUTION

SSM Firestop Mortar

SpecSeal® SSM Firestop Mortar is a lightweight and economical solution for large openings in concrete floors and walls. SpecSeal® Mortar mixes with water to form a slurry that can be pumped, poured, or troweled into the opening. SpecSeal® Mortar is quick setting to allow forms to be removed faster.

Features & Benefits

- Can be poured, pumped, or troweled in place
- Combines with other SpecSeal® Firestop Products
- Durable, permanent seal



ORDERING INFORMATION

Catalog Number	UPC Number	Description	Packaging	Weight (Each)	Nom. Yield (Mixed)
SSM106	730573041062	SpecSeal® Series SSM Firestop Mortar	Poly Pail	22.87 lbs (10.37 kg)	1,225 in ³ (20.1 L)
SSM22B	730573042007	SpecSeal® Series SSM Firestop Mortar	Fiber Bag	22.41 lbs (10.17 kg)	1,225 in ³ (20.1 L)

TEST STANDARDS: ASTM E814 (UL1479), CAN/ULC-S115

Pale Red
Color

Permanent
Solution



1-800-992-1180
stifirestop.com



[Click here to learn more about](#)



ZSTI3541 11121