



INTUMESCENT WRAP FOR PLASTIC PIPE

Intumescent Wrap Strip

SpecSeal® SSW Wrap Strips are available in a variety of sizes and types to tackle any combustible penetration. SSW Wrap Strips are available in 12 ft. rolls as well as individually pre-sized strips to minimize waste and speed up installation. When installed in conjunction with restraining steel, SSW Wrap Strips are able to collapse non-metallic piping of up to 12 in. diameter!

Features & Benefits

- Water-resistant - no soluble or hygroscopic ingredients
- Economical - 12' (3.7 m) rolls or precut strips means no piecing, less waste
- Highly flexible - no foil, easier to install
- Versatile - performer for a wide range of complex applications
- Tested in a variety of construction types
- Partners with other SpecSeal® Firestop Products



ORDERING INFORMATION

Catalog Number	UPC Number	Size	(UOM) Qty.	Case Qty.	Weight (Each)
SSW1569	730573037980	12' x 1-1/2" x 11/16" (3.7 m x 38 mm x 17.5 mm) roll	1	6	6.31 lbs (2.86 kg)
SSW2538	730573037973	12' x 2-1/2" x 3/8" (3.7 m x 64 mm x 9.5 mm) roll	1	6	6.93 lbs (3.14 kg)
SSW375-12	730573037966	12' x 1-1/2" x 3/8" (3.7 m x 38 mm x 9.5 mm) roll	1	12	3.71 lbs (1.68 kg)
SSWRC2	730573037522	1-1/2" width 30 Gauge sheet metal restraining collar for ≤6" (152 mm) trade size pipe, 25' (7.6 m) roll	1	1	5.19 lbs (2.35 kg)
SSWRC3	730573037553	2-1/2" width 30 Gauge sheet metal restraining collar for 8" (204 mm) trade size pipe, 25' (7.6 m) roll	1	1	6.40 lbs (2.90 kg)

PRECUT WRAP STRIPS

SSW125	730573031254	1-1/2" (38 mm) x 1/8" (3.2 mm) strip sized for 2" (51 mm) trade size pipe	1	540	0.07 lbs (0.03 kg)
SSW250	730573032503	1-1/2" (38 mm) x 1/4" (6.4 mm) strip sized for 3" (76 mm) trade size pipe	1	160	0.21 lbs (0.10 kg)
SSW375	730573033753	1-1/2" (38 mm) x 3/8" (9.5 mm) strip sized for 4" (102 mm) trade size pipe	1	150	0.40 lbs (0.18 kg)

TEST STANDARDS: ASTM E814 (UL 1479), CAN/ULC-S115



1-800-992-1180
stofirestop.com



[Click here to learn more about](#)



ZSTI3503 01521