

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

Product identifier used on the label:

Sto Dispersion Adhesive Product Name:

Product Code: 80829 SDS Manufacturer Number: 80829

Other means of identification:

None. Synonyms:

Recommended use of the chemical and restrictions on use:

Product Use/Restriction: Waterbased Acrylic Adhesive.

 $\underline{\hbox{Chemical manufacturer address and telephone number:}}\\$ Manufacturer Name: Sto Corp.

6175 Riverside Drive, SW Atlanta, Georgia 30331

General Phone Number: (404) 346-3666

Emergency phone number:

(800) 424-9300 Emergency Phone Number:

SECTION 2: HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with CFR 1910.1200(d)(f):

GHS Pictograms:

Signal Word: WARNING

GHS Class: Eye Irritation. Category 2. Skin Irritation. Category 2

Acute Oral Toxicity. Category 4.

Hazard Statements:

Causes serious eye irritation. Causes skin irritation. Harmful if swallowed.

Precautionary Statements: Wash hands thoroughly after handling.

Wash hallos thologying after inallining.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

IF ON SKIN: Wash with plenty of water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see ... on this label).

Rinse mouth.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Dispose of contents/container in accordance with Local, State, Federal and Provincial regulations.

Hazards not otherwise classified that have been identified during the classification process:

Route of Exposure: Eves. Skin. Inhalation, Ingestion.

Potential Health Effects:

Eye: May cause irritation. Skin: May cause irritation.

Inhalation: Prolonged or excessive inhalation may cause respiratory tract irritation.

Normal application procedures for this product pose no hazard as to the release of respirable titanium dioxide dust, but grinding or sanding dried films of this product may yield some respirable titanium

Ingestion: Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Eyes. Skin. Respiratory system. Digestive system. Target Organs:

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures:

Chemical Name CAS# **Ingredient Percent** EC Num.

Sto Dispersion Adhesive 80829 Revision: 10/26/2016 Page 1 of 5

14808-60-7 60 - 100 by weight 238-878-4 Crystaline silica (Quartz)

Water 7732-18-5 10 - 30 by weight 231-791-2

Acrylic polymer 10 - 30 by weight No Data

SECTION 4: FIRST AID MEASURES

Description of necessary measures:

Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of Eye Contact:

the eyes by separating the eyelids with fingers. Get immediate medical attention

Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists. Skin Contact:

If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained Inhalation:

personnel. Seek immediate medical attention

 $If \ swallowed, \ do \ NOT \ induce \ vomiting. \ Call \ a \ physician \ or \ poison \ control \ center \ immediately. \ Never \ give$ Ingestion:

Most important symptoms/effects, acute and delayed:

First Responders should provide for their own safety prior to rendering assistance.

SECTION 5: FIRE FIGHTING MEASURES

Suitable and unsuitable extinguishing media:

Use dry chemical or foam when fighting fires involving this material. Water mist may be used to cool closed containers. Suitable Extinguishing Media:

Unusual Fire Hazards: Material may spatter above 100 °C/212 °F.

Special protective equipment and precautions for fire-fighters:

Protective Equipment: As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent)

and full protective gear.

Fire Fighting Instructions: Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible,

contain fire run-off water.

NFPA Ratings:

NFPA Health: 1 NFPA Flammability: 1 n NFPA Reactivity:



SECTION 6 : ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Personal Precautions: Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.

Environmental precautions:

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

Methods and materials for containment and cleaning up:

Methods for containment: Contain spills with an inert absorbent material such as soil, sand or oil dry.

Methods for cleanup: Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container.

Provide ventilation. Clean up spills immediately observing precautions in the protective equipment

SECTION 7: HANDLING and STORAGE

Precautions for safe handling:

Handling: Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.

Hygiene Practices: Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep

container tightly closed when not in use. Store away from direct heat or sunlight, sources of UV radiation, peroxides, or free radicals

Sto Dispersion Adhesive

Revision: 10/26/2016

Do not store in temperatures above 49°C (120 °F) or below 9°C (48 °F). Keep away from direct

sunlight.

Specific end use(s):

Work Practices: Handle in accordance with good industrial hygiene and safety practices.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE GUIDELINES:

Crystaline silica (Quartz):

Guideline ACGIH: TLV-TWA: 0.025 mg/m3 (R)

Appropriate engineering controls:

Engineering Controls: Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other

engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance

of the personal protective equipment.

Individual protection measures:

Eye/Face Protection: Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye

and face protection regulation, or the European standard EN 166.

Skin Protection Description: Wear appropriate protective gloves and other protective apparel to prevent skin contact. Consult manufacturer's data for permeability data.

Hand Protection Description: Nitrile rubber or natural rubber gloves are recommended.

Respiratory Protection:

A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower

safety station.

PPE Pictograms:



Only established PEL and TLV values for the ingredients are listed.

SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL AND CHEMICAL PROPERTIES:

Physical State Appearance: Liquid. Odor: Sliaht.

Boiling Point: Not determined. 0°C (32°F) Melting Point:

Specific Gravity:

Solubility: Miscible in water. Vapor Density: Not determined. Vapor Pressure: Not determined. Percent Volatile: Data not available. Evaporation Rate: Not determined. pH: 7.5 - 10

Flash Point: Not determined. Lower Flammable/Explosive Limit: Not determined Upper Flammable/Explosive Limit: Not determined. Auto Ignition Temperature: Not determined.

SECTION 10: STABILITY and REACTIVITY

Chemical Stability:

Chemical Stability: Stable under recommended handling and storage conditions.

Possibility of hazardous reactions:

Hazardous Polymerization: Hazardous polymerization does not occur.

Conditions To Avoid:

Conditions to Avoid: Heat, flames, ignition sources, and sparks. Incompatible materials, Freezing or temperatures below

80829

0°C (32°F).

Incompatible Materials:

Incompatible Materials: Water reactive materials

Sto Dispersion Adhesive Revision: 10/26/2016 Page 3 of 5 Special Decomposition Products: Thermal decomposition can lead to release irritant fumes and toxic gases.

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:

Crystaline silica (Quartz):

RTECS Number: VV7330000

Inhalation: Inhalation - Rat TCLo - Lowest published toxic concentration: 248 mg/m3/6H [Lungs, Thorax, or

Initiation - Act TCLO - Lowest published toxic concentration: 248 mg/m3/on [Lungs, Florax, or Respiration - Other changes Biochemical - Metabolism (intermediary) - Other proteins Biochemical - Metabolism (intermediary) - Effect on inflammation or mediation of inflammation]

Inhalation - Rat TCLO - Lowest published toxic concentration: 248 mg/m3/6H [Lungs, Thorax, or Respiration - Changes in lung weight Immunological Including Allergic - Increase in cellular immune response Biochemical - Metabolism (intermediary) - Effect on inflammation or mediation of

Inhalation - Rat TCLo - Lowest published toxic concentration : 200 mg/kg [Lungs, Thorax, or Respiration - Fibrosis, focal (pneumoconiosis) Lungs, Thorax, or Respiration - Other changes Nutritional and Gross Metabolic - Changes in iron]

Inhalation - Mouse TCLo - Lowest published toxic concentration : 40 mg/kg [Lungs, Thorax, or Respiration - Other changes]
Inhalation - Mouse TCLo - Lowest published toxic concentration : 40 mg/kg [Immunological Including

Allergic - Decrease in cellular immune response]

Inhalation - Rat TCLo - Lowest published toxic concentration : 1 mg/kg (RTECS)

Oral - Rat TDLo - Lowest published toxic dose : 120 gm/kg [Gastrointestinal - Hypermotility, diarrhea Gastrointestinal - Other changes] (RTECS) Ingestion:

Chronic Effects: Prolonged and repeated inhalation of respirable crystalline silica can cause silicosis, a chronic lung

disease characterized by fibrosis and scarring of the lung tissue resulting in a decrease in lung function, breathlesness, wheezing, coughing and sputum production.

Carcinogenicity: Crystalline silica in the form of quartz or cristobalite dust causes cancer of the lung.. Normal application

procedures for this product pose no hazard as to the release of crystalline silica dust, but grinding or sanding dried films of this product may yield some respirable crystalline silica.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Ecotoxicity: No ecotoxicity data was found for the product. Environmental Fate: No environmental information found for this product.

SECTION 13: DISPOSAL CONSIDERATIONS

Description of waste:

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous

waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines. Triple-rinse drum prior to offering for recycle, reconditioning or disposal. Dispose of rinsate in an environmentally acceptable manner consistent with applicable waste management.

SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Non regulated. DOT Hazard Class: Non regulated.

IATA Shipping Name: Non regulated.

IMDG UN Number: Non regulated.

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product:

This product does not contain any chemicals which are subject to the reporting requirements of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III (40CFR, Part 372). SARA:

California PROP 65: The following statement(s) are provided under the California Safe Drinking Water and Toxic

Enforcement Act of 1986 (Proposition 65): WARNING! This product contains a chemical known to the State of California to cause cancer.

Canada WHMIS:

EU Class:

In accordance to Regulation (EC) No 1272/2008 on the classification, labelling and packaging of

substances and mixtures.

Risk Phrases: R36/37/38 - Irritating to eyes, respiratory system and skin.

Safety Phrase: S23 - Do not breathe gas/fumes/vapour/spray.

Sto Dispersion Adhesive 80829 Revision: 10/26/2016 Page 4 of 5 S37 - Wear suitable gloves.

<u>Crystaline silica (Quartz)</u>:

TSCA Inventory Status: Listed

Canada DSL: Listed

EC Number: 238-878-4

Water:

TSCA Inventory Status: Listed

Canada DSL: Listed

EC Number: 231-791-2

SECTION 16: ADDITIONAL INFORMATION

HMIS Ratings:

HMIS Health Hazard: 1
HMIS Fire Hazard: 1
HMIS Reactivity: 0
HMIS Personal Protection: X

| Health Hazard | 1 |
|---------------------|---|
| Fire Hazard | 1 |
| Physical Hazard | 0 |
| Personal Protection | х |

SDS Creation Date: August 16, 2013
SDS Revision Date: October 26, 2016
MSDS Revision Notes: Format Update

SDS Format:

Disclaimer:

The information and recommendations contained herein are, to the best of Sto Corp.'s knowledge and belief, accurate and reliable as of the date issued. Sto Corp. does not warrant or guarantee their accuracy or reliability, and Sto Corp. shall not be liable for any loss or damage arising out of their use thereof. The information and recommendations are offered for the users' consideration and examination, and it is the users' responsibility to satisfy itself that they are suitable and complete for its particular use.

Copyright© 1996-2015 Actio Corporation. All Rights Reserved.

Sto Dispersion Adhesive
Revision: 10/26/2016