


Sto Stucco Mesh

81556 Sto Stucco Mesh



Technical Data	
Nominal Weight, oz/yd ² (g/m ²)	1.9 (45.1)
Construction	Tri-Directional Laid Scrim
Minimum Tensile Strength Machine Direction, lb/in (N/cm)	68 (119)
Features	Benefits
1 Alkali-resistant	Compatible with cement-based materials
2 Fiberglass-based	High tensile strength

Sto Stucco Mesh is a tri-directional weave, flexible treated glass fiber mesh for use with portland cement stucco brown coats in vertical above grade wall construction.

Coverage

440 ft² per 38 inch wide roll (44.1 m²), with allowance for overlaps. Does not include waste.

Packaging

Four 150 ft x 38 in (45.7 x 0.96 m) rolls per box

Shelf Life

2 years in original, properly stored, unopened container.

Storage

Store in a dry area off the ground in cartons with cartons on side (not upright). Storage on ends may lead to crumpled, wrinkled or creased mesh that may be difficult to work with. Protect from direct sunlight.

Sto Stucco Mesh

Application

Apply Sto Stucco Mesh to freshly placed stucco brown coat. Embed mesh using a stainless-steel trowel. Smooth out any wrinkles, forcing the mesh down and covering it with fresh material.

At all mesh joints, overlap the Sto Stucco Mesh at least 2.5 inches (64 mm). Trim all loose or frayed edges.

Limitations

- Not for use in StoTherm ci or other EIF systems. Use only with portland cement stucco brown coats in vertical above grade wall construction.

Health And Safety

Health Precautions

Contains fiberglass. Avoid breathing dust. As with any chemical construction product, exercise care when handling.

WARNING!

Causes eye irritation. Causes skin irritation.

Precautionary Statements:

Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

FIRST AID MEASURES

Eye Contact: Flush with warm running water for 15 minutes. Do not rub. If irritation persists, consult a physician.

Skin Contact: Wash with mild soap and running water. Use a wash cloth to help remove fibers. If irritation persists, consult a physician.

Inhalation: Glass fibers may cause mechanical irritation to the mouth, nose and throat. Remove person to fresh air.

Ingestion: Unlikely entry route. If symptoms develop, consult a physician.

Spills

Collect and dispose of in accordance with local, state or federal regulations..

Disposal

Dispose of in accordance with local, state or federal regulations.

Warning

KEEP CONTAINERS CLOSED WHEN NOT IN USE. KEEP OUT OF THE REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION. FOR INDUSTRIAL USE ONLY. Consult the Safety Data Sheet (SDS) on www.stocorp.com for further health and safety information.

LIMITED WARRANTY

This product is subject to a written limited warranty which can be obtained free of charge from Sto Corp.

Sto Corp.
3800 Camp Creek Parkway
Building 1400, Suite 120
Atlanta, GA 30331

Tel: 404-346-3666
Toll Free: 1-800-221-2397
Fax: 404 346-3119

www.stocorp.com

S155-81556
Revision Number: A1.0
Date: 11/2016

Attention

This product is intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. It should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of this product or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to this product, and to the structure of the building or its components. **STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME.** For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, www.stocorp.com.