

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

Product identifier used on the label:

Product Name: Sto Watertight Coat White Component B

81242-025 Product Code: SDS Manufacturer Number: 81242-025

Other means of identification:

Synonyms: None.

Recommended use of the chemical and restrictions on use:

Product Use/Restriction: Polymer Modified Cementitious Based Groundcoat/Adhesive.

Chemical manufacturer address and telephone number: Manufacturer Name:

6175 Riverside Drive, SW Address: Atlanta, Georgia 30331

General Phone Number: (404) 346-3666

Emergency phone number:

Emergency Phone Number: (800) 424-9300

SECTION 2: HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with CFR 1910.1200(d)(f):

GHS Pictograms:







Signal Word: DANGER.

Serious Eye Damage. category 1. Skin Irritation. Category 2. GHS Class:

Acute Oral Toxicity. Category 4.

Hazardous to the aquatic environment, short term, acute, category 1.

Hazard Statements: Causes serious eye damage. Causes skin irritation.

Harmful if swallowed. Very toxic to aquatic life.

Precautionary Statements:

Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

IF ON SKIN: Wash with plenty of water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician. Specific treatment (see ... on this label).

Rinse mouth.

If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Collect spillage.
Dispose of contents/container in accordance with Local, State, Federal and Provincial regulations.

Hazards not otherwise classified that have been identified during the classification process:

Route of Exposure: Eyes. Skin. Inhalation. Ingestion.

Potential Health Effects:

Eve: May cause irritation, burns and permanent tissue damage. Skin: May cause irritation, dry skin, redness, discomfort or burns.

Inhalation: Prolonged or repeated inhalation may cause lung damage.

Prolonged and repeated inhalation of respirable crystalline silica can cause silicosis, a chronic lung disease characterized by fibrosis and scarring of the lung tissue resulting in a decrease in lung

Product Code: 81242-025

function, breathlesness, wheezing, coughing and sputum production.

Ingestion: May cause irritation. Ingesting large amounts may cause injury.

Signs/Symptoms: Product is alkali when wet, excessive and prolonged exposure can cause severe irritation, burns and

permanent tissue damage.

Sto Watertight Coat White Component B Revision:: 10/26/2016

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures:

Chemical Name CAS# **Ingredient Percent** EC Num.

65997-15-1 Portland cement 100 by weight 266-043-4

The structure of Portland cement may contain the following in some concentration ranges:

The structure of Portland cement may contain the following in some concentration ranges: Calcium Notes:

oxide, silica quartz, chromium, gypsum, limestone, and magnesium oxide

The structure of Portland cement may contain the following in some concentration ranges:

SECTION 4: FIRST AID MEASURES

Description of necessary measures:

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of

the eyes by separating the eyelids with fingers. Get immediate medical attention.

Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists. Skin Contact:

If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained Inhalation:

personnel. Seek immediate medical attention.

If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give Ingestion:

anything by mouth to an unconscious person.

SECTION 5: FIRE FIGHTING MEASURES

Suitable and unsuitable extinguishing media:

Suitable Extinguishing Media: Use extinguishing measures that are appropriate to local circumstances and the surrounding

environment.

Specific hazards arising from the chemical:

Hazardous Combustion Byproducts:

Oxides of carbon, oxides of nitrogen and other organic substances may be formed.

Special protective equipment and precautions for fire-fighters:

Protective Equipment: As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent)

and full protective gear.

NFPA Ratings:

NFPA Health: 2 NFPA Flammability: 0

0 NFPA Reactivity:



SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Personal Precautions: Use proper personal protective equipment as listed in Section 8. Evacuate area and keep unnecessary

and unprotected personnel from entering the spill area.

Environmental precautions:

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

Methods and materials for containment and cleaning up:

Methods for containment: Contain spills with an inert absorbent material such as soil, sand or oil dry.

Methods for cleanup: Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container.

Provide ventilation. Clean up spills immediately observing precautions in the protective equipment

Product Code: 81242-025

section.

SECTION 7: HANDLING and STORAGE

Precautions for safe handling:

Handling: Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing.

Hygiene Practices: Wash thoroughly after handling. Avoid contact with eyes and skin, Avoid inhaling vapor or mist.

Special Handling Procedures: Material is alkaline when mixed with water. Use precaution and proper protective equipment

Conditions for safe storage, including any incompatibilities:

Storage: Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep

container tightly closed when not in use.

Specific end use(s):

Work Practices:

Use good laboratory practice when working with chemicals. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety

shower.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE GUIDELINES:

Portland cement:

Guideline ACGIH: TLV-TWA: 1 mg/m3 (E,R)

TLV-TWA: 1 mg/m3 Respirable fraction (R) Guideline OSHA: PEL-TWA: 5 mg/m3 Respirable fraction (R)

PEL-TWA: 50 mppcf Total particulate/dust (T) PEL-TWA: 15 mg/m3 Total particulate/dust (T)

Appropriate engineering controls:

Good general ventilation should be sufficient to control airborne levels. Otherwise, use appropriate **Engineering Controls:**

engineering control such as process enclosures, local exhaust ventilation, or other engineering controls including use of a biosafety cabinet / fume hood to control airborne levels below recommended

exposure limits.

Individual protection measures:

Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye Eye/Face Protection:

and face protection regulation, or the European standard EN 166.

Skin Protection Description: Protective laboratory coat, apron, or disposable garment recommended.

Hand Protection Description: Use impervious gloves. Nitrile gloves are recommended.

Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be

permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Other Protective: Follow good industrial hygiene practices when handling this material.

General Hygiene Considerations: Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

PPE Pictograms:



Notes : Only established PEL and TLV values for the ingredients are listed.

SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL AND CHEMICAL PROPERTIES:

Physical State Appearance: Solid or powder.

Color: White

Odor: Little to no odor. **Boiling Point:** > 1832 °F (>1000 °C)

Melting Point: Not determined.

Specific Gravity: 2.3 to 3.1

Specific Volume: Not determined.

Solubility: 0.1 TO 1.0% in water.

Vapor Density: Not applicable. Vapor Pressure: Not applicable. Percent Volatile: Not applicable. Evaporation Rate: Not determined.

Not determined. Viscosity:

> Sto Watertight Coat White Component B Revision:: 10/26/2016

Flash Point: No information.

Flash Point Method: Data not available. Lower Flammable/Explosive Limit: Data not available. Upper Flammable/Explosive Limit: Data not available. Auto Ignition Temperature: Data not available. VOC Content: Not determined.

SECTION 10: STABILITY and REACTIVITY

Chemical Stability:

Chemical Stability: Stable under normal temperatures and pressures.

Possibility of hazardous reactions:

Hazardous Polymerization: Will not occur.

Conditions To Avoid:

Conditions to Avoid: Avoid high temperature condition. Avoid contact with incompatible materials.

Incompatible Materials:

Incompatible Materials: Not applicable.

Hazardous Decomposition Products:

Special Decomposition Products: Oxides of carbon, oxides of nitrogen and other organic substances may be formed.

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:

Portland cement:

RTECS Number: VV8770000

Eye: No relevant toxicological data for classification were found. No relevant toxicological data for classification were found. Inhalation: No relevant toxicological data for classification were found. No relevant toxicological data for classification were found. Ingestion: Sensitization: No relevant toxicological data for classification were found. Target Organ Repeated

Exposures:

No relevant toxicological data for classification were found.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Ecotoxicity: No ecotoxicity data was found for the product. Environmental Fate: No environmental information found for this product.

SECTION 13: DISPOSAL CONSIDERATIONS

Description of waste:

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines,

if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines. Triple-rinse drum prior to offering for recycle, reconditioning or disposal. Dispose of rinsate

in an environmentally acceptable manner consistent with applicable waste management.

Product Code: 81242-025

SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Non regulated. DOT Hazard Class: Non regulated.

IATA Shipping Name: Non regulated.

IMDG UN Number: Non regulated.

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product:

SARA: This product contains chemicals which are subject to the reporting requirements of the Superfund

Amendments and Reauthorization Act of 1986 (SARA) Title III (40CFR, Part 372).

California PROP 65: The following statement(s) are provided under the California Safe Drinking Water and Toxic

Enforcement Act of 1986 (Proposition 65): WARNING! This product contains a chemical known to the State of California to cause cancer.

Portland cement:

TSCA Inventory Status: Listed Canada DSL: Listed 266-043-4 EC Number:

SECTION 16: ADDITIONAL INFORMATION

HMIS Ratings:

HMIS Health Hazard: 2 HMIS Fire Hazard: HMIS Reactivity: 0 **HMIS Personal Protection:** Х

Health Hazard Fire Hazard Reactivity 0 **Personal Protection** X

SDS Creation Date: September 08, 2015 SDS Revision Date: October 26, 2016 Format Update SDS Revision Notes:

SDS Format:

Disclaimer:

The information and recommendations contained herein are, to the best of Sto Corp.'s knowledge and belief, accurate and reliable as of the date issued. Sto Corp. does not warrant or guarantee their accuracy or reliability, and Sto Corp. shall not be liable for any loss or damage arising out of their use thereof. The information and recommendations are offered for the users' consideration and examination, and it is the users' responsibility to satisfy itself that they are suitable and complete for

Product Code: 81242-025

its particular use.

Copyright© 1996-2018 Enviance. All Rights Reserved.

Sto Watertight Coat White Component B Revision:: 10/26/2016