



Building with conscience.

| Exterior | Coatings |



## **StoColor® Acryl Flat & StoColor® Acryl Plus** High-performance, weather resistant acrylic topcoats.

To find a better 100% acrylic topcoat, you have to look beneath the surface. StoColor® Acryl Flat and StoColor® Acryl Plus offer more than other products on the market. And, of course, both are backed by our Sto warranty, one of the best in the industry. Take a closer look at StoColor® Acryl Flat and StoColor® Acryl Plus and you'll see the difference.

# StoColor® Acryl Flat & StoColor® Acryl Plus

The topcoats that do so much more than just lie there.



## StoColor® Acryl Flat

A high-performance 100% acrylic topcoat, StoColor® Acryl Flat is designed to provide superior protection against sun, salt, wind, rain and corrosion. Vapor permeable with high solids content, this proven solution allows the substrate to breathe naturally, resisting blisters and mold caused by moisture. Plus, StoColor® Acryl Flat offers exceptional fade resistance and complies with EPA and SCAQMD VOC requirements.

## StoColor® Acryl Plus

StoColor® Acryl Plus delivers all of the benefits of StoColor® Acryl... PLUS so much more! Featuring a higher build, it passes wind-driven rain tests<sup>2</sup> and can be used on both horizontal and vertical applications. For greater flexibility and broader color matching options, StoColor® Acryl Plus is our top choice in topcoats.

Feature	Benefit
Vertical and Horizontal Application	One product for multiple purposes
High Build <sup>1</sup>	Excellent durability
High Grade / Durable	Heavy duty - extended time between repainting
CO <sub>2</sub> Diffusion Resistance / Corrosion Resistance	Protects embedded reinforcing steel against corrosion
Weather Resistant	Protects against severe sun, heat, humidity, dirt and rain
Low VOC	Safe for workers and the environment
Vapor Permeable	Allows substrate to breathe naturally; resists blisters and mold caused by moisture
Flexible	Resists cracking
Mold / Mildew Resistant	Resists mildew growth
Wind Driven Rain Tested <sup>1,2</sup>	Repels water; increases service life of substrate
Excellent Color Retention	Stays attractive longer

<sup>1</sup> StoColor® Acryl Plus <sup>2</sup> ASTM D 6904 (formerly Fed Spec TT-555 B) - no water penetration with 2 coats or 1 coat and primer after 24 hour water spray and dynamic pressure.

## Which is right for your project?

	StoColor® Acryl Flat (80201)	StoColor® Acryl Plus (80648)
CO <sub>2</sub> Diffusion Resistance	***	***
Horizontal Application	NR	***
Fade Resistance	**	***
Commercial Warranty	**	***
Solids Content	55	53
Low VOC	Yes	Yes
High Build	**	***
Salt & Sun Resistance	**	***

\* = Good    \*\* = Better    \*\*\* = Best  
NR = Not Recommended

## Sto Corp.

3800 Camp Creek Parkway  
Building 1400, Suite 120,  
Atlanta, GA. 30331

Tel: 404-346-3666  
Toll Free: 1-800-221-2397  
Fax: 404-346-3119  
[www.stocorp.com](http://www.stocorp.com)



Building with conscience.

For more information on StoColor® Acryl Flat or StoColor® Acryl Plus, visit [www.stocorp.com](http://www.stocorp.com) or contact your local Sto Sales Representative or Sto Distributor.

### ATTENTION

Sto products are intended for use by qualified professional contractors, not consumers, as a component of a larger construction assembly as specified by a qualified design professional, general contractor or builder. They should be installed in accordance with those specifications and Sto's instructions. Sto Corp. disclaims all, and assumes no, liability for on-site inspections, for its products applied improperly, or by unqualified persons or entities, or as part of an improperly designed or constructed building, for the nonperformance of adjacent building components or assemblies, or for other construction activities beyond Sto's control. Improper use of Sto products or use as part of an improperly designed or constructed larger assembly or building may result in serious damage to Sto products, and to the structure of the building or its components. STO CORP. DISCLAIMS ALL WARRANTIES EXPRESSED OR IMPLIED EXCEPT FOR EXPLICIT LIMITED WRITTEN WARRANTIES ISSUED TO AND ACCEPTED BY BUILDING OWNERS IN ACCORDANCE WITH STO'S WARRANTY PROGRAMS WHICH ARE SUBJECT TO CHANGE FROM TIME TO TIME. For the fullest, most current information on proper application, clean-up, mixing and other specifications and warranties, cautions and disclaimers, please refer to the Sto Corp. website, [www.stocorp.com](http://www.stocorp.com).