StoPrime Sand ®



According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015). Date of Issue: 01/04/2023 Version: 2.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture Product Name (s): StoPrime Sand [®] Product Identifier: 80801

1.2. Intended Use of the Product

Use Of The Substance/Mixture: Primer

1.3. Name, Address, and Telephone of the Responsible Party

Company

Sto Corp. 6175 Riverside Drive SW Atlanta, GA 30331 (800)221-2397

www.stocorp.com

1.4. Emergency Telephone Number Emergency Number : 800-424-9300 CHEMTREC

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA Classification		
Skin Sens. 1A	H317	
Carc. 1A	H350	
STOT RE 1	H372	
Full text of hazard cl	asses and H-statements : see section 16	

2.2. Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)

Signal Word (GHS-US/CA)	GH507 GH508 : Danger
Hazard Statements (GHS-US/CA)	: H317 - May cause an allergic skin reaction.
	H350 - May cause cancer (inhalation).
	H372 - Causes damage to organs (respiratory system) through prolonged or repeated
	exposure (inhalation).
Precautionary Statements (GHS-US/CA)	: P201 - Obtain special instructions before use.
	P202 - Do not handle until all safety precautions have been read and understood.
	P260 - Do not breathe vapors, mist, or spray.
	P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
	P270 - Do not eat, drink or smoke when using this product.
	P272 - Contaminated work clothing should not be allowed out of the workplace.
	P280 - Wear protective gloves, protective clothing, and eye protection.
	P302+P352 - IF ON SKIN: Wash with plenty of water.
	P308+P313 - If exposed or concerned: Get medical advice/attention.
	P314 - Get medical advice/attention if you feel unwell.
	P321 - Specific treatment (see section 4 on this SDS).
	P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
	P362+P364 - Take off contaminated clothing and wash it before reuse.
	P405 - Store locked up.
	P501 - Dispose of contents/container in accordance with local, regional, national, and
	international regulations.





According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No additional information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Synonyms	Product Identifier	% *	GHS Ingredient Classification
Calcium Carbonate	Chalk / Limestone (A noncombustible solid characteristic of sedimentary rock. It consists primarily of calcium carbonate.) / Natural calcium carbonate / Marble / Calcium carbonate / Limestone (sedimentary rock) / Calcite / Limestone ground / Acetate, 4- methyl-2-propyl-2H- tetrahydropyran-4-yl / Ground limestone	(CAS-No.) 1317-65-3	30-60	Not classified
Quartz	Quartz (SiO2) / Silica, crystalline, quartz / Crystalline silica, quartz / .alphaQuartz / Silica, crystalline, .alpha quartz / QUARTZ / Crystalline silica in the form of quartz / Quartz, silica / Quartz (respirable fraction) / Silica dust / Silica, crystalline- .alpha.quartz / Silica, .alpha quartz / Silicon dioxide / Silica, quartz / Silica, crystalline / Quartz (crystalline silica) / Silica dust, crystalline / QUARTZ POWDER / Silica, crystalline (quartz)	(CAS-No.) 14808-60-7	10-30	Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372
Titanium dioxide Or talc	C.I. 77891 / C.I. Pigment White 6 / Titanium oxide (TiO2) / Cl 77891 / Titanium(IV) oxide / C.I. Pigment White 7 / Pigment White 6 / Titanium dioxide nanoparticles / Titanium oxide / Titanium dioxide(2)	(CAS-No.) 13463-67-7	2-10	Carc. 2, H351
Water	H20	(CAS-No.) 7732-18-5	30-60	Not Classified
Nonhazardous Acrylic polymers	Not available	No Data	5-10	Not Classified

Full text of H-statements: see section 16

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. If exposed or concerned: Get medical advice/attention. Wash affected area with soap and water for at least 15 minutes. Obtain medical attention if irritation/rash develops or persists.

Eye Contact: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for at least 15 minutes. Obtain medical attention.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Causes damage to organs (respiratory organs) through prolonged or repeated exposure (inhalation). May cause cancer (inhalation) Inhalation is not an expected route of exposure during normal use of this product.

Inhalation: Prolonged exposure may cause irritation. <u>Accelerated Silicosis</u> can occur with exposure to high concentrations of respirable crystalline silica over a relatively short period; lung lesions can appear within five years of the initial exposure. The progression can be rapid. Accelerated silicosis is similar to chronic or ordinary silicosis, except that lung lesions appear earlier and the progression is more rapid.

<u>Acute Silicosis</u> can occur with exposures to very high concentrations of respirable crystalline silica over a very short time period, sometimes as short as a few months. The symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis can be fatal.

Skin Contact: May cause slight irritation.

Eye Contact: May cause slight irritation to eyes.

Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: May cause cancer (inhalation). Causes damage to organs (respiratory organs) through prolonged or repeated exposure (inhalation). This product contains crystalline silica. Long term exposure to respirable crystalline silica results in a significant risk of developing silicosis; a seriously disabling and fatal lung disease, and other non-malignant respiratory disease, lung cancer, kidney effects, and immune system effects.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Quartz (silica) will dissolve in hydroflouric acid producing a corrosive gas, silicon tetrafluoride.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Metal oxides. Sulfur oxides. Nitrogen oxides. Silicon oxides. Acrid smoke and irritating fumes. Acrolein.

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe dust. Do not get in eyes, on skin, or on clothing. Do not handle until all safety precautions have been read and understood.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Recover the product by vacuuming, shoveling or sweeping. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Do not get in eyes, on skin, or on clothing.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

No use is specified.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Titanium dioxide (13463-67-	7)		
USA ACGIH	ACGIH OEL TWA	10 mg/m ³	
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen	
USA OSHA	OSHA PEL (TWA) [1]	15 mg/m ³ (total dust)	
USA NIOSH	NIOSH REL (TWA)	2.4 mg/m ³ (CIB 63-fine)	
		0.3 mg/m ³ (CIB 63-ultrafine, including engineered	
		nanoscale)	
USA IDLH	IDLH	5000 mg/m ³	
Alberta	OEL TWA	10 mg/m ³	
British Columbia	OEL TWA	10 mg/m ³ (total dust)	
		3 mg/m ³ (respirable fraction)	
Manitoba	OEL TWA	10 mg/m ³	
New Brunswick	OEL TWA	10 mg/m ³	
Newfoundland & Labrador	OEL TWA	10 mg/m ³	
Nova Scotia	OEL TWA	10 mg/m ³	
Nunavut	OEL STEL	20 mg/m ³	
Nunavut	OEL TWA	10 mg/m ³	
Northwest Territories	OEL STEL	20 mg/m ³	
Northwest Territories	OEL TWA	10 mg/m ³	
Ontario	OEL TWA	10 mg/m ³	
Prince Edward Island	OEL TWA	10 mg/m ³	
Québec	VEMP (OEL TWA)	10 mg/m ³ (containing no Asbestos and <1% Crystalline	
		silica-total dust)	
Saskatchewan	OEL STEL	20 mg/m ³	
Saskatchewan	OEL TWA	10 mg/m ³	
Yukon	OEL STEL	20 mg/m ³	
Yukon	OEL TWA	30 mppcf	
		10 mg/m ³	
Quartz (14808-60-7)			

01/04/2023



Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

	ACGIH OEL TWA	tions And According To The Hazardous Products Regulation (February 11, 2015). 0.025 mg/m ³ (respirable particulate matter)
USA ACGIH	ACGIH chemical category	A2 - Suspected Human Carcinogen
USA OSHA	OSHA PEL (TWA) [1]	50 μg/m ³ (Respirable crystalline silica)
USA OSHA	OSHA PEL (TWA) [1]	$(250)/(\%SiO_2+5)$ mppcf TWA (respirable fraction)
USA USHA		(10)/(%SiO ₂ +2) mg/m ³ TWA (respirable fraction)
		(For any operations or sectors for which the respirable
		crystalline silica standard, 1910.1053, is stayed or
		otherwise not in effect, See 20 CFR 1910.1000 TABLE Z-3)
USA NIOSH	NIOSH REL (TWA)	0.05 mg/m ³ (respirable dust)
USA IDLH	IDLH	50 mg/m ³ (respirable dust)
Alberta	OEL TWA	0.025 mg/m ³ (respirable particulate)
British Columbia	OEL TWA	0.025 mg/m ³ (respirable)
Manitoba	OEL TWA	0.025 mg/m ³ (respirable particulate matter)
New Brunswick	OEL TWA	0.1 mg/m ³ (respirable fraction)
Newfoundland & Labrador	OEL TWA	0.025 mg/m ³ (respirable particulate matter)
Nova Scotia	OEL TWA	0.025 mg/m ³ (respirable particulate matter)
Nunavut	OEL TWA	0.05 mg/m ³ (respirable fraction (Silica - crystalline)
Northwest Territories	OEL TWA	0.05 mg/m ³ (respirable fraction (Silica - crystalline)
Ontario	OEL TWA	0.1 mg/m ³ (designated substances regulation-respirable
		fraction (Silica, crystalline)
Prince Edward Island	OEL TWA	0.025 mg/m ³ (respirable particulate matter)
Québec	VEMP (OEL TWA)	0.1 mg/m ³ (respirable dust)
Saskatchewan	OEL TWA	0.05 mg/m ³ (Trydimite removed-respirable fraction (Silica -
		crystalline (Trydimite removed))
Yukon	OEL TWA	300 particle/mL (Silica - Quartz, crystalline)
Limestone (1317-65-3)	·	
USA OSHA	OSHA PEL (TWA) [1]	15 mg/m ³ (total dust)
		5 mg/m ³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA)	10 mg/m ³ (total dust)
		5 mg/m ³ (respirable dust)
Alberta	OEL TWA	10 mg/m ³
British Columbia	OEL STEL	20 mg/m ³ (total)
British Columbia	OEL TWA	10 mg/m ³ (total dust)
		3 mg/m ³ (respirable fraction)
New Brunswick	OEL TWA	10 mg/m ³ (particulate matter containing no Asbestos and
		<1% Crystalline silica)
Nunavut	OEL STEL	20 mg/m ³
Nunavut	OEL TWA	10 mg/m ³
Northwest Territories	OEL STEL	20 mg/m ³
Northwest Territories	OEL TWA	10 mg/m ³
Québec	VEMP (OEL TWA)	10 mg/m ³ (Limestone, containing no Asbestos and <1%
		Crystalline silica-total dust)
Saskatchewan	OEL STEL	20 mg/m ³
Saskatchewan	OEL TWA	10 mg/m ³
Yukon	OEL STEL	20 mg/m ³
Yukon	OEL TWA	30 mppcf 10 mg/m ³
Silica, cristobalite (14464-46	-1)	
USA ACGIH	ACGIH OEL TWA	0.025 mg/m ³ (respirable particulate matter)
USA ACGIH	ACGIH chemical category	Suspected Human Carcinogen
USA OSHA	OSHA PEL (TWA) [1]	50 μg/m ³ (Respirable crystalline silica)
USA OSHA	OSHA PEL (TWA) [2]	(1/2)(250)/(%SiO ₂ +5) mppcf (respirable fraction)
01/04/2022	·····/ [-]	



Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

		(1/2)(10)/(%SiO ₂ +2) mg/m ³ (respirable fraction)
		(For any operations or sectors for which the respirable
		crystalline silica standard, 1910.1053, is stayed or
		otherwise not in effect, See 29 CFR 1910.1000 TABLE Z-3)
USA NIOSH	NIOSH REL (TWA)	0.05 mg/m ³ (respirable dust)
USA IDLH	IDLH	25 mg/m ³ (respirable dust)
Alberta	OEL TWA	0.025 mg/m ³ (respirable particulate)
British Columbia	OEL TWA	0.025 mg/m ³ (respirable)
Manitoba	OEL TWA	0.025 mg/m ³ (respirable particulate matter)
New Brunswick	OEL TWA	0.05 mg/m ³ (respirable fraction)
Newfoundland & Labrador	OEL TWA	0.025 mg/m ³ (respirable particulate matter)
Nova Scotia	OEL TWA	0.025 mg/m ³ (respirable particulate matter)
Nunavut	OEL TWA	0.05 mg/m ³ (respirable fraction (Silica - crystalline)
Northwest Territories	OEL TWA	0.05 mg/m ³ (respirable fraction (Silica - crystalline)
Ontario	OEL TWA	0.05 mg/m ³ (designated substances regulation-respirable
		fraction (Silica, crystalline)
Prince Edward Island	OEL TWA	0.025 mg/m ³ (respirable particulate matter)
Québec	VEMP (OEL TWA)	0.05 mg/m ³ (respirable dust)
Saskatchewan	OEL TWA	0.05 mg/m ³ (Trydimite removed-respirable fraction (Silica -
		crystalline (Trydimite removed))
Yukon	OEL TWA	150 particle/mL (Silica)

8.2. Exposure Controls

Appropriate Engineering Controls: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective eye wear (safety glasses with side shields). Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics are recommended as a best practice.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Protective eye wear (safety glasses with side shields are recommended).

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties		
: Liquid/Paste		
: No data available		
: Slight		
: No data available		
: 7.5 -10.0		
: No data available		
: No data available		
: 32 Fahrenheit		
: No data available		

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Flammability (solid, gas)	: No data available
Lower Flammable Limit	: No data available
Upper Flammable Limit	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: No data available
Specific Gravity	: >1
Solubility	: Miscible in water
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity:

Quartz (silica) will dissolve in hydroflouric acid producing a corrosive gas, silicon tetrafluoride.

10.2. Chemical Stability:

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions:

Hazardous polymerization will not occur.

10.4. Conditions to Avoid:

Direct sunlight, extremely high or low temperatures, and incompatible materials. Avoid dust formation.

10.5. Incompatible Materials:

Strong acids, strong bases, strong oxidizers.

10.6. Hazardous Decomposition Products:

Thermal decomposition may produce: Carbon oxides (CO, CO₂). Metal oxides. Sulfur oxides. Nitrogen oxides. Silicon oxides. Acrid smoke and irritating fumes. Acrolein.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data:

No additional information available

Skin Corrosion/Irritation: Not classified

Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: Not classifed.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: May cause cancer.

Specific Target Organ Toxicity (Repeated Exposure): Lungs

Reproductive Toxicity: Not classified.

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation. <u>Accelerated Silicosis</u> can occur with exposure to high concentrations of respirable crystalline silica over a relatively short period; lung lesions can appear within five years of the initial exposure. The progression can be rapid. Accelerated silicosis is similar to chronic or ordinary silicosis, except that lung lesions appear earlier and the progression is more rapid.

<u>Acute Silicosis</u> can occur with exposures to very high concentrations of respirable crystalline silica over a very short time period, sometimes as short as a few months. The symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis can be fatal.

Symptoms/Injuries After Skin Contact: Not classified. May cause slight irritation with prolonged use.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: May cause cancer (inhalation), Causes damage to organs (respiratory organs) through prolonged or repeated exposure (inhalation), Suspected of damaging fertility or the unborn child, This product contains crystalline silica. Long term exposure



According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

to respirable crystalline silica results in a significant risk of developing silicosis; a seriously disabling and fatal lung disease, and other non-malignant respiratory disease, lung cancer, kidney effects, and immune system effects

11.2. Information on Toxicological Effects - Ingredient(s)

11.2. Information on roxicological effects - ingre	
LD50 and LC50 Data:	
Titanium dioxide (13463-67-7)	
LD50 Oral Rat	> 10000 mg/kg
LC50 Inhalation Rat	5.09 mg/l/4h
Quartz (14808-60-7)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 5000 mg/kg
Titanium dioxide (13463-67-7) or Talc	
IARC Group	2B
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Quartz (14808-60-7)	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Silica, amorphous, diatomaceous earth (68855-54-9)	
IARC Group	3
Silica, cristobalite (14464-46-1)	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Not classified.

12.2. Persistence and Degradability

Sto Primer		
Persistence and Degradability Not established.		
12.3. Bioaccumulative Potential		
Sto Primer		
Bioaccumulative Potential Not established.		
Silica, amorphous, diatomaceous earth (68855-54-9)		
CF Fish 1 (no known bioaccumulation)		

12.4. Mobility in Soil

No additional information available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Not regulated for transport

14.2. In Accordance with IMDG



According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Not regulated for transport

14.3. In Accordance with IATA

Not regulated for transport

14.4. In Accordance with TDG

Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

SARA Section 311/312 Hazard Classes	Health hazard - Carcinogenicity
	Health hazard - Reproductive toxicity
	Health hazard - Specific target organ toxicity (single or repeated
	exposure)
	Health hazard - Respiratory or skin sensitization

Titanium dioxide (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Quartz (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Limestone (1317-65-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Silica, cristobalite (14464-46-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

15.2. US State Regulations

California Proposition 65

WARNING: This product can expose you to Titanium dioxide, which is known to the State of California to cause cancer, and Lithium carbonate, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Titanium dioxide (13463-67-7)	Х			
Quartz (14808-60-7)	Х			
Silica, cristobalite (14464-46-1)	Х			

Titanium dioxide (13463-67-

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

Quartz (14808-60-7)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

Limestone (1317-65-3)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

Silica, cristobalite (14464-46-1)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

15.3. Canadian Regulations

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Titanium dioxide (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List)

Quartz (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

Limestone (1317-65-3)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Silica, cristobalite (14464-46-1)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision : 2.0 Other Information : 01/04/2023

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

GHS Full Text Phrases:

Carc. 1A	Carcinogenicity Category 1A	
Carc. 1B	Carcinogenicity Category 1B	
Carc. 2	Carcinogenicity Category 2	
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1	
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	
H302	Harmful if swallowed	
H335	May cause respiratory irritation	
H350	May cause cancer	
H351	Suspected of causing cancer	
H372	Causes damage to organs through prolonged or repeated exposure	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)