## COOLRIDGE®

## SECTIONAL RIDGE VENT

## DESCRIPTION

	<ul> <li>COOLRIDGE® is an injection-molded polypropylene sectional ridge vent with external baffles.</li> <li>18 square inches of net free area per linear foot.</li> <li>25-40 year Limited Warranty and Arbitration Agreement (depending on shingle installed).</li> <li>Internal supports in nail line area provide compression resistance for nailing.</li> <li>Embossed nail line and 1/2" nail zone area with clear space underneath help facilitate proper nailing.</li> <li>Exterior baffles and internal "sinewave"-shaped baffles help keep rain and snow out.</li> <li>Male/female connection between pieces helps protect seams from leaks.</li> <li>Vent holes are only 1/8" wide to help prevent insect infiltration.</li> <li>Drain holes every 4" in exterior baffle to prevent water build-up.</li> <li>USES: Used to help properly ventilate attic space when used in conjunction with soffit vents. For slopes above 12 inches per foot, call for technical services at 1-800-641-4691.</li> </ul>				
	BUILDINGS EXPERIENCE HOW LONG VENTILATION WARRANTY THAT INCLU CONDITIONS WHICH AR	S BEGIN TO AGE AS SOON A AGING FACTORS DIFFEREN PRODUCTS WILL LAST. THA DES A BINDING ARBITRATIO E INCORPORATED HEREIN D WARRANTY AT TAMKO.C	ITLY, SO IT IS DIFFI I'S WHY TAMKO PR ON CLAUSE AND O BY REFERENCE.	CULT TO PREDICT OVIDES A LIMITED THER TERMS AND YOU MAY OBTAIN	
REQUIREMENTS					
	<ul> <li>Must be used with an equal or greater amount of soffit ventilation.</li> </ul>				
	<ul> <li>Minimum 3/12 roof pitch (up to 16/12).</li> </ul>				
	<ul> <li>Use with standard 12" wide cap shingles.</li> </ul>				
TECHNICAL INFORMATION	Use provided 2-1/2" nails to assure penetration of at least 3/4" into decking.				
	Florida Building Code Appro	oved: FL4103	}		
PRODUCT DATA	Meets or exceeds requirements of Texas Dept. of Insurance RV-28				
Information included in this product data sheet was current at time of printing.	Width <sup>†</sup>	14-3/4"			
	Height <sup>†</sup>	13/16"			
To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800–641–4691.	Length <sup>†</sup>	48" long			
	12 Pieces per bundle	48 ft. per package			
	Color	Black			

<sup>†</sup>Subject to manufacturing variation



P.O. Box 1404 Joplin, MO 64802-1404 800-641-4691 tamko.com



**IMPORTANT SAFETY INFORMATION:** Do not install until all appropriate safety precautions have been read and understood. <u>The TAMKO Safety Data Sheet (SDS)</u> is available at tamko.com/sds. Always use appropriate fall protection equipment and wear appropriate personal protective equipment (PPE) when working with this product. Moisture, frost, debris or other material will decrease the traction and can cause slippery conditions when walking on the product. **Applicator safety is of utmost importance.**