

# TECTUM® TECTUM High NRC

Square Lay-in  
coarse texture




CONTAIN CLEAN PROTECT



CAD/Revit® drawings at:  
[armstrongceilings.com/cadrevit](http://armstrongceilings.com/cadrevit)

plus capabilities  
to do more



▲ Tectum Lay-in 24" x 24" panels in White with Prelude® XL® 15/16" suspension system

[armstrongceilings.com/capabilities](http://armstrongceilings.com/capabilities)  
See more photos at:  
[armstrongceilings.com/photogallery](http://armstrongceilings.com/photogallery)

Tectum® Lay-in and Tectum Lay-in High NRC ceiling panels provide durable, sustainable, acoustical options for a wide variety of applications.

## KEY SELECTION ATTRIBUTES

- new** • Tectum Lay-in now has UL® Certified acoustics with acoustical testing and reporting that align with industry-wide best practices
- new** • Tectum High NRC panels have a proprietary, factory-applied acoustical backer, adding sound absorption that is certified by UL
- new** • CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim (standard colors only)
- Tectum panels are part of the Sustain® portfolio and meet the most stringent industry sustainability standards today – 1" panels in White and Natural only
- Excellent sound absorption - NRC up to 0.85 (1" High NRC panel)
- Mold and mildew-resistant surface
- Durable for heavy-use interiors
- Wide variety of color options available, including custom colors
- Can be field painted up to six times without impacting acoustic or fire performance
- Short lead times
- USDA Biobased content: 98%

**COLORS** Due to printing limitations, shade may vary from actual product.



\* For Tectum Lay-in only. Made-to-order, custom color panels, and any panels greater than 1" thick are not included in Sustain portfolio.

## DETAILS



1. Tectum Lay-in
2. Tectum Lay-in with Prelude® 15/16" suspension system
3. Tectum Lay-in High NRC proprietary acoustical backer

Note: Panel edges are unfinished. Custom color panel edges are fully painted.

# TECTUM® TECTUM High NRC

Square Lay-in  
coarse texture



For LEED contribution visit  
armstrongceilings.com/greenie



## VISUAL SELECTION

armstrongceilings.com/catdws	Susp. Item Dwg. No. ◆	Dimensions Nominal W x L x H (Inches)
TECTUM® Square Lay-in (FSC® Certified)	1 8184T10_ _ _	24 x 24 x 1" □
	8183T10_ _ _	24 x 48 x 1" □
	Other Size Panels*	1", 1-1/2", or 2" thickness
TECTUM® High NRC Square Lay-in (FSC-certified)	1 5340W2L02T10_ _ _	24 x 24 x 1" □
	15/16" Square Lay-in	5340W2L04T10_ _ _

◆ When specifying or ordering, include the appropriate 3-digit color suffix TNA = Natural TWH = White (e.g. 8184T10 I W H)  
\* 1-1/2" and 2" thicknesses require a back rabbet cut to make room for the suspension system; see diagram below.

NOTE: Four-sided beveled edge panels are recommended in adjoining panel installations.

## PERFORMANCE

Dots represent high level of performance.


Fire Rating	Light Reflect	Anti-Mold/Mildew	Sag Resist	Certified Low VOC Emissions	Fog	Impact	Scratch	30-Yr Warranty
Class Up to A 0.75	•	•	•	•	•	•	•	•
Class Up to A 0.75	•	•	•	•	•	•	•	•
Class Up to A 0.75	•	•	N/A	•	•	•	•	•
Class Up to A 0.75	•	•	•	•	•	•	•	•

## ACOUSTICAL INFORMATION


Item No.	Infill Panel Item No.	NRC	+ CAC	=	NRC + CAC	Total Acoustics¹
8184T10_ _ _	N/A	0.40	N/A	N/A	N/A	
8183T10_ _ _	N/A	0.40	N/A	N/A	N/A	
5340W2L02T10_ _ _	N/A	0.85	N/A	N/A	N/A	
5340W2L04T10_ _ _	N/A	0.85	N/A	N/A	N/A	
8184T10_ _ _	1713	0.90	33	N/A		
8183T10_ _ _	1713	0.90	33	N/A		

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.  
**GOOD** (NRC 0.60-0.65; CAC 35+)  
**BETTER** (NRC 0.70-0.75; CAC 35+)  
**BEST** (NRC 0.80+; CAC 35+)

## SUSPENSION SYSTEMS



## ACCESSORIES



Tectum Hold-Down Clip  
8178T10 – 1" Panel Thickness  
8178T20 – 1-1/2" Panel Thickness  
Attaches to main beams and cross tees behind lay-in ceilings; helps prevent panel displacement from non-deliberate contact by basketballs and other forces from below the ceiling.

## ACOUSTICAL INFILL PANELS

Item No.	Description	Dimensions	Color	Pcs/Ctn
1713	School Zone® Fine Fissured Lay-in Acoustical Panel	24 x 24 x 3/4"	White	12

## PHYSICAL DATA

**Material**  
Cementitious Wood Fiber; FSC-certified. For more information about FSC-certified fire-retardant products, or to view our FSC-certification letter, contact TechLine at 1 877 276 7876.  
Tectum High NRC panels have an acoustical fleece.  
**Surface Finish**  
Factory-applied latex paint with silicate surface coating for abuse resistance. Natural is unpainted.  
**Fire Performance**  
Class A per IBC. Flame Spread Index 25 or less and Smoke Developed Index 50 or less when tested in accordance with ASTM E84.  
CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less and Smoke Developed Index of 50 or less.  
**VOC Emissions**  
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189, ANSI/GBI Green Building Assessment Protocol.

**Humidity/Sag Resistance**  
HumiGuard® Plus panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.  
**Anti-Mold/Mildew**  
Ceiling panels with BioBlock® performance resist the growth of mold and mildew on the panel surface.  
**Installation Considerations**  
Use caution and wear appropriate hand, eye, and dust mask protection when cutting and installing Tectum panels. Refer to installation instructions for complete details and cutting recommendations.  
**Primary (Embodied) Energy**  
See all LCA information on our EPDs.  
**Application Considerations**  
Color variation among panels is common due to the natural characteristics of the wood on White and Natural panels.  
Wood fibers may appear orange on Natural colored panels due to the characteristics of the wood.  
**Design Support**  
Project management assistance is available by calling TechLine at 1 877 276 7876.

**Specification Consideration**  
FSC-certified panels available upon request.  
Attention: For FSC-certified wood products to maintain their CoC certification, products must be sold to a CoC-certified distributor or directly to the installing contractor. Failure to do so breaks the CoC.  
**Seismic Restraint**  
Tectum Lay-in panels are approved for application in all seismic areas when installed per Armstrong Ceilings Installation Instructions.  
**Cleaning and Disinfecting**  
Cleaning and CDC recommended disinfecting options available on armstrongceilings.com/cleaning  
**Warranty**  
30-Year Performance Guarantee and Warranty when installed with Armstrong® Suspension System. Details at armstrongceilings.com/warranty  
**Weight: Square Feet/Carton**  
1" – 1.65 lbs/SF  
1-1/2" – 2.53 lbs/SF  
2" – 3.3 lbs/SF  
8183T10 – 4 pcs/ctn  
8184T10 – 8 pcs/ctn  
5340W2L02T10 – 8 pcs/ctn  
5340W2L04T10 – 4 pcs/ctn

TechLine / 1 877 276-7876  
armstrongceilings.com/tectumlayin  
BPCS-5615-821

LEED® is a registered trademark of the U.S. Green Building Council; Declare® and Living Building Challenge™ (LBC) are trademarks of the International Living Future Institute™; WELL™ and WELL Building Standard™ are trademarks of the International WELL Building Institute; FSC® is a registered trademark of FSC Forest Stewardship Council, A.C., license code FSC-C007626; Revit® is a registered trademark of Autodesk, Inc.; UL and UL Certified are registered trademarks of UL LLC; all other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates © 2021 AWI Licensing LLC



TECTUM® WOOD FIBER – Standard

