


# (CA) Clip Angles



### **Product Data:**

- Designation: SA Length (L) x gauge.
- Designed for 3-5/8, 4, 6, 7-1/4, 8, 9-1/4, 10 and 12 inch studs.
- Gauges: 18 ga (3-5/8, 4, or 6 inch only),
  14 ga (all lengths), 12 ga (6, 7-1/4, 8, 9-1/4, 10 and 12 inch only)
- W and F dimensions per request. Standard 2" x 2"

#### **Uses:**

- For miscellaneous attachments of intersecting framing components.
- For attachment of joist framing components to flush mounted headers.
- For attachment of solid blocking sections to adjacent studs of joists.
- For alternate screw attachment of CRC briding to stud webs in lieu direct weld

# J Bead



### L Bead



### **Product Data:**

- Sturdy, channel-type steel casing.
- · Joint cement applied to front side.
- L Bead available in both regular and long-leg flange.
- Easily installs to framing or jamb.

#### **Uses:**

- Provides maximum protection.
- · Adds a finished edge to wallboard at window and door jambs

Product	Size Depth	Length(ft.)	Pcs./Ctn.	Ft./Ctn.
L-50, J-50	1/2" or 5/8"	8', 10'	63, 50 5	04, 500
L-62, J-62	<i>u</i>	<i>u</i>	"	"

Custom lengths and UPC labeling available upon request.

# (RT) Reveal Trim



#### **Product Data:**

- · An economical steel channel.
- · No joint cement required.

## Uses:

 Provides edge protection around doors and windows or any partition junction openings.

Product	Size Depth	Length(ft.)	Pcs./Ctn.	Ft./Ctn.
RT-50, RT-62	1/2" & 5/8"	8', 10'	63, 50	504, 500

Custom lengths and UPC labeling available upon request.

# **093 Expansion Control Joint**



#### **Product Data:**

- Manufactured from the highest quality pure zinc coil stock for superior corrosion resistance.
- Fits standard 1/4" openings.

### **Uses:**

• Product is excellent for interior or exterior applications.

Product	Length(ft.)	Pcs./Ctn.	Ft./Ctn.	
093	10'	25	250	