


(CA) Clip Angles



Product Data:

- Designation: SA Length (L) x gauge.
- Designed for 3-5/8, 4, 6, 7-1/4, 8, 9-1/4, 10 and 12 inch studs.
- Gauges: 18 ga (3-5/8, 4, or 6 inch only),
 14 ga (all lengths), 12 ga (6, 7-1/4, 8, 9-1/4, 10 and 12 inch only)
- W and F dimensions per request. Standard 2" x 2"

Uses:

- For miscellaneous attachments of intersecting framing components.
- For attachment of joist framing components to flush mounted headers.
- For attachment of solid blocking sections to adjacent studs of joists.
- For alternate screw attachment of CRC briding to stud webs in lieu direct weld

J Bead



L Bead



Product Data:

- Sturdy, channel-type steel casing.
- · Joint cement applied to front side.
- L Bead available in both regular and long-leg flange.
- Easily installs to framing or jamb.

Uses:

- Provides maximum protection.
- · Adds a finished edge to wallboard at window and door jambs

| Product | Size Depth | Length(ft.) | Pcs./Ctn. | Ft./Ctn. |
|------------|--------------|-------------|-----------|----------|
| L-50, J-50 | 1/2" or 5/8" | 8', 10' | 63, 50 5 | 04, 500 |
| L-62, J-62 | <i>u</i> | <i>u</i> | " | '' |

Custom lengths and UPC labeling available upon request.

(RT) Reveal Trim



Product Data:

- · An economical steel channel.
- · No joint cement required.

Uses:

 Provides edge protection around doors and windows or any partition junction openings.

| ı | Product | Size Depth | Length(ft.) | Pcs./Ctn. | Ft./Ctn. |
|---|--------------|-------------|-------------|-----------|----------|
| ı | RT-50, RT-62 | 1/2" & 5/8" | 8', 10' | 63, 50 | 504, 500 |

Custom lengths and UPC labeling available upon request.

093 Expansion Control Joint



Product Data:

- Manufactured from the highest quality pure zinc coil stock for superior corrosion resistance.
- Fits standard 1/4" openings.

Uses:

• Product is excellent for interior or exterior applications.

| Product | Length(ft.) | Pcs./Ctn. | Ft./Ctn. | |
|---------|-------------|-----------|----------|--|
| 093 | 10' | 25 | 250 | |