

GENERAL USE



DUPLEX (SCAFFOLD)

- Double Head
- Diamond Point
- Round Smooth Shank

For temporary construction where nail removal is required such as concrete form work, scaffolds and bracing. Also used for stringing temporary wiring.

DUPLEX - BRIGHT							
Item #	Size	Length	Gauge	Head	Weight	Nails/lb	UPC
1AJ16	6d	1¾"	11.5	1 ⁵ / ₆₄ "	50 lb	152	95832000625
1AJ22	8d	2¼"	10.25	¼"	50 lb	89	95832000632
1AJ24	9d	2½"	10.25	¼"	50 lb	81	95832000649
1AJ26	10d	2¾"	9	1 ⁹ / ₆₄ "	50 lb	62	95832000656
1AJ30	16d	3"	8	5/16"	50 lb	48	95832000663
1AJ32	18d	3¼"	7	1 ¹ / ₃₂ "	50 lb	38	95832000670
1AJ34	20d	3½"	6	3/8"	50 lb	31	95832000687
1AJ40	30d	4"	5	3/8"	50 lb	23	95832000694



RING SHANK POLE BARN

- Flat Head
- Diamond Point
- Round Ringed Shank

For load-bearing wooden structures where superior holding power is necessary. Threads lock to wood fibres to add structural strength.

POLE BARN - TEMPER HARDENED							
Item #	Size	Length	Gauge	Head	Weight	Nails/lb	UPC
7P304	20d	4"	7	3/8"	50 lb	35	95832007365
7P305	40d	5"	7	3/8"	50 lb	28	95832007372
7P306	60d	6"	5	1 ⁵ / ₃₂ "	50 lb	17	95832007389