

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC FC GRAY - 30 CTG CS
Material: 960712 323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Carcinogenicity	Category 1A
Toxic to reproduction	Category 1B

Unknown toxicity - Health

Acute toxicity, oral	13.62 %
Acute toxicity, dermal	16.37 %
Acute toxicity, inhalation, vapor	99.62 %
Acute toxicity, inhalation, dust or mist	99.91 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 2
--	------------

Unknown toxicity - Environment

Acute hazards to the aquatic environment	44.5 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: May cause cancer.
May damage fertility or the unborn child.
Toxic to aquatic life.

Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Response: IF exposed or concerned: Get medical advice/attention.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients
--

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	30 - 60%
Butyl benzyl phthalate	85-68-7	10 - 30%
Calcium Carbonate (Limestone)	1317-65-3	7 - 13%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	1 - 5%
Stearic acid	57-11-4	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Talc	14807-96-6	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact: Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.

Eye contact: Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: No data available.

Methods and material for containment and cleaning up: Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities: Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Stearic acid - Respirable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Stearic acid - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Talc - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
Talc	TWA	20 millions of	US. OSHA Table Z-3 (29 CFR 1910.1000)

		particles per cubic foot of air	(2000)
Talc - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

Chemical name	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Diisodecyl phthalate	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Vinyltrimethoxysilane	STEL	10 ppm 60 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Talc - Respirable.	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Talc	TWA	2 fibers/mL	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Talc - Respirable fraction.	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Talc - Respirable dust.	TWA	3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Appropriate Engineering Controls Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear suitable protective clothing.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use.

9. Physical and chemical properties

Appearance

Physical state: solid

Form: Paste

Color: Gray

Odor: Mild

Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: No data available.

Flash Point: No data available.

Evaporation rate: Slower than n-Butyl Acetate

Flammability (solid, gas): No

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): No data available.

Flammability limit - lower (%): No data available.

Explosive limit - upper (%): No data available.

Explosive limit - lower (%): No data available.

Vapor pressure: No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and in the bottom of containers.

Relative density:	1.5257
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Alcohols. Amines. Strong acids. Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information**Information on likely routes of exposure**

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 25,250.16 mg/kg

Dermal

Product: ATEmix: 4,308 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide Overall evaluation: Possibly carcinogenic to humans.

Hydrotreated heavy naphthenic distillate Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

Talc Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity

Product: May damage fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.

Aquatic Invertebrates
Product: No data available.

Chronic hazards to the aquatic environment:

Fish
Product: No data available.

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants
Product: No data available.

Persistence and Degradability

Biodegradation
Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Mobility in soil:

No data available.

Other adverse effects:

Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:

Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging:

No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Butyl Benzyl Phthalate), 9, PG III, MARINE POLLUTANT

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Butyl benzyl phthalate	100 lbs.
Dibutyl phthalate	10 lbs.
Methanol	5000 lbs.
Acetic acid	5000 lbs.
Diethyl phthalate	100 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Butyl benzyl phthalate	100 lbs.
Diisodecyl phthalate	
Dibutyl phthalate	10 lbs.
Diisodecyl phthalate (mixed Is)	
Methanol	5000 lbs.
Acetic acid	5000 lbs.
Diethyl phthalate	100 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Calcium carbonate	10000 lbs
Butyl benzyl phthalate	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Calcium oxide	10000 lbs
Titanium dioxide	10000 lbs
Stearic acid	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Talc	10000 lbs

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Calcium carbonate
Butyl benzyl phthalate
Calcium Carbonate (Limestone)
Calcium oxide
Titanium dioxide
Hydrotreated heavy naphthenic distillate
Talc

US. Massachusetts RTK - Substance List

Chemical Identity

Calcium carbonate
Butyl benzyl phthalate
Calcium Carbonate (Limestone)
Calcium oxide
Titanium dioxide
Crystalline Silica (Quartz)/ Silica Sand
Diethyl phthalate

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Calcium carbonate
Butyl benzyl phthalate
Calcium Carbonate (Limestone)
Diisodecyl phthalate
Calcium oxide
Titanium dioxide

US. Rhode Island RTK

Chemical Identity

Calcium carbonate
Calcium Carbonate (Limestone)
Calcium oxide
Titanium dioxide

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and exempt solvent) : 6 g/l
VOC Method 310 : 0.39 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision
--

Revision Date: 11/30/2018

Version #: 2.1

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.