



Tremco Commercial Sealants & Waterproofing
3735 Green Road
Beachwood, OH 44122
US: 800.852.9068
Canada: 800.363.3213
www.tremcosealants.com

Tremco Incorporated certifies that Tremco Elastomeric Sheeting (uncured neoprene sheeting) meets the physical properties outlined in the Tremco Incorporated published data sheets, specifications, and application instructions. This product has been tested against the following ASTM methods as shown herein:

Elastomeric Sheeting

Uncured Neoprene Sheeting

TYPICAL PHYSICAL PROPERTIES		
Property	Test Method	Result
Thickness, Inches	ASTM-D412	Gauge $\pm 10\%$
Width, Inches	ASTM-D751	Size $\pm 1/8, -0$
Length, Feet	ASTM-D751	Size $+ 1, -0$
Tensile Strength (After Vulcanization)	ASTM-D412 DIE C	1484
Elongation	ASTM-D412 DIE C	400
Modulus, 100% Min %	ASTM-D412 DIE C	25-75
Tear Resistance lbs/in min.	ASTM-D412 DIE C	171
Brittleness Point @ -40°F	ASTM-D2137	Does not Break
Ozone Resistance 168 Hrs/100pphm/104°F/50%EXT.	ASTM-D1149	No Cracks @7X Magnification
Water Absorption, Max. Mass % 166 Hrs. @ 158°F	ASTM-D471	+8.5