

Tremco Commercial Sealants & Waterproofing 3735 Green Road Beachwood, OH 44122 US: 800.852.9068

Canada: 800.363.3213 www.tremcosealants.com



September 30, 2020

To Whom It May Concern:

RE: ExoAir 230—Green Building Product Information (LEED v4.1 Information)

Tremco Incorporated is an organization that is committed to quality, our employees, and our environment. We are responsive to both internal and external customers, and we pledge to treat everyone with good stewardship and respect.

Tremco Incorporated certifies the following for ExoAir 230:

## **Building Product Disclosure and Optimization:**

ExoAir 230 is manufactured in Toronto, Ontario, Canada.

No single extracted material is used to produce the majority of this product.

Recycled content for ExoAir 230 is not available, and for the purposes of LEED reporting should be assumed to be zero.

### **Low Emitting Materials - VOC Content Information:**

ExoAir 230 is an air barrier with a VOC content of 35g/L equaling 1% as applied/mixed. As such, VOC levels are lower than the limits set by SCAQMD rule 1113.

Note: VOC content values are as reported for the highest VOC content color for all ExoAir 230 colors. Other colors may have a lower VOC content reported on their SDS.

This product is Greenguard certified, meaning it has met some of the world's most difficult and complete standards for low emissions of VOC's into indoor air. This product also adheres to the California Department of Public Health (CDPH) Standard Method V1.1-2010, a standard vital to demonstrate compliance with LEED.

#### **Green Chemistry:**

Tremco Incorporated is dedicated to the environment and prides itself on making its products as sustainable as possible. We are pleased to report that this product is produced without any Red List chemicals. As such, it can be used to assist in finishing projects aimed towards achieving a Living Building Challenge certification.



Tremco Commercial Sealants & Waterproofing 3735 Green Road Beachwood, OH 44122 US: 800.852.9068 Canada: 800.363.3213

www.tremcosealants.com

# Manufacture Inventory (reported to 1000ppm):

| Chemical Name or Role          | CAS Number | Amount | GHS Hazard    |
|--------------------------------|------------|--------|---------------|
| Waterbased Polymer Resin       |            | 30-70% | Non-Hazardous |
| White mineral oil              | 8042-47-5  |        |               |
| Amorphous silica               | 7631-86-9  |        |               |
| Propylene glycol               | 57-55-6    |        |               |
| Titanium dioxide               | 13463-67-7 |        |               |
| Adhesion Promoter              |            | <1%    | Non-Hazardous |
| Talc                           | 14807-96-6 |        |               |
| Ammonium hydroxide             | 1336-21-6  |        |               |
| Moisture Scavenger             |            | <1%    | Non-Hazardous |
| Zinc oxide                     | 1314-13-2  |        |               |
| Fungicide                      |            | <1%    | Non-Hazardous |
| Chlorothalonil                 | 1897-45-6  |        |               |
| Aromatic petroleum distillates | 64742-95-6 |        |               |
| Surfactant                     |            | <1%    | Non-Hazardous |

## **Additional Information:**

Air barrier systems, when properly installed, have been shown to reduce energy costs for HVAC by as much as 40% versus buildings without fully-adhered air barriers. Should you have any questions or require additional information, please do not hesitate to contact Technical Services or your local Tremco Field Representative.

Sincerely,

Joe Kravetz

**Product Steward** 

**Compliance and Regulatory Affairs**