

Revision Date: 08/05/2016

SAFETY DATA SHEET

1. Identification

Material name: TREMCO POLYURETHANE FOAM CLEANER - 12/CS

Material: 001922GC501

Recommended use and restriction on use

Recommended use: Sealant Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants 3735 Green Road Beachwood OH 44122 US

Contact person:EH&S DepartmentTelephone:216-292-5000

Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Serious Eye Damage/Eye Irritation Category 2A
Germ Cell Mutagenicity Category 1B
Carcinogenicity Category 1A

Unknown toxicity - Health

Acute toxicity, oral 30 %
Acute toxicity, dermal 30 %
Acute toxicity, inhalation, vapor 100 %
Acute toxicity, inhalation, dust or mist 100 %

Unknown toxicity - Environment

Acute hazards to the aquatic 30 % environment Chronic hazards to the aquatic 100 %

environment

Label Elements

Hazard Symbol:





Revision Date: 08/05/2016

Signal Word: Danger

Hazard Statement: Extremely flammable aerosol.

Causes serious eye irritation. May cause genetic defects.

May cause cancer.

Pressurized container: May burst if heated.

Precautionary Statement: Prevention:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective

equipment as required.

Response: If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical

advice/attention.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122

°F. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Acetone	67-64-1	60 - 100%
Propane	74-98-6	15 - 40%
Butane	106-97-8	5 - 10%
Isobutane	75-28-5	5 - 10%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Rinse mouth thoroughly.

Inhalation: Move to fresh air.

Skin Contact: Remove contaminated clothing and wash the skin thoroughly with soap and

water after work.



Revision Date: 08/05/2016

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a

protected location. Move containers from fire area if you can do so without

risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash

back.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep

Stop the flow of material, if this is without risk. Absorb with sand or other

upwind.

Methods and material for containment and cleaning up:

inert absorbent.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so.



Revision Date: 08/05/2016

7. Handling and storage

Precautions for safe handling:

Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Conditions for safe storage, including any incompatibilities:

Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values		Source
Acetone	TWA	250 ppm		US. ACGIH Threshold Limit Values (03 2015)
	STEL	500 ppm		US. ACGIH Threshold Limit Values (03 2015)
	PEL	1,000 ppm	2,400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Propane	PEL	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Butane	STEL	1,000 ppm		US. ACGIH Threshold Limit Values (02 2013)
Isobutane	STEL	1,000 ppm		US. ACGIH Threshold Limit Values (02 2013)

Chemical name	type	Exposure Limit Values	Source
Acetone	STEL	500 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	250 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Acetone	TWAEV	500 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	750 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)



Revision Date: 08/05/2016

Acetone	STEL	1,000 ppm	2,380 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	TWA	500 ppm	1,190 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Propane	TWA	1,000 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Propane	TWAEV	1,000 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Propane	TWA	1,000 ppm	1,800 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Butane	STEL	750 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	600 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Butane	TWAEV	800 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Butane	TWA	800 ppm	1,900 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isobutane	TWA	1,000 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isobutane	TWAEV	800 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Biological Limit Values

Diological Ellint Talaco		
Chemical Identity	Exposure Limit Values	Source
Acetone (acetone:	25 mg/l (Urine)	ACGIH BEI (03 2015)
Sampling time: End of shift)		

Appropriate Engineering Controls

No data available.



Revision Date: 08/05/2016

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general

ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable

level.

Eye/face protection: Wear safety glasses with side shields (or goggles).

No data available.

Skin Protection

Other:

Hand Protection: No data available.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. Avoid contact with eyes. When

using do not smoke.

9. Physical and chemical properties

Appearance

Physical state: Aerosols
Form: Aerosols
Color: Colorless

Odor: Strong petroleum/solvent

Odor threshold:

pH:

No data available.

Plash Point:

Por °C -143 °F

Evaporation rate:

Slower than Ether

Flammability (solid, gas): Yes
Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

Explosive limit - lower (%):

No data available.

No data available.

Vapor pressure:

No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 0.699

Solubility(ies)

Solubility in water: Practically Insoluble



Revision Date: 08/05/2016

Solubility (other):

Partition coefficient (n-octanol/water):

Auto-ignition temperature:

Decomposition temperature:

Viscosity:

No data available.

No data available.

No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and

chromates).

Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

Skin Contact: Moderately irritating to skin with prolonged exposure.

Eye contact: Causes serious eye irritation.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: No data available.

Dermal

Product: No data available.

Inhalation

Product: No data available.

Specified substance(s):

Acetone LC 50 (Rat, 4 h): 76 mg/l

Propane LC 50 (Rat, 4 h): > 13023 ppm



Revision Date: 08/05/2016

Butane LC 50 (Rat, 4 h): > 13023 ppm

Isobutane LC 50 (Rat, 4 h): > 13023 ppm

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Acetone in vivo (Rabbit): Experimental result, Supporting study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Acetone in vivo (Rabbit, 24 hrs): Minimum grade of severe eye irritant

Propane Irritating

Butane Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.



Revision Date: 08/05/2016

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Acetone LC 50 (Fathead minnow (Pimephales promelas), 96 h): 5,490 - 7,030 mg/l

Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Acetone LC 50 (Water flea (Daphnia magna), 24 h): 10 mg/l Mortality

EC 50 (Water flea (Daphnia magna), 48 h): 21,600 - 23,900 mg/l Intoxication

LC 50 (Scud (Gammarus fasciatus), 96 h): > 100 mg/l Mortality

LC 50 (Asiatic clam (Corbicula manilensis), 96 h): > 20,000 mg/l Mortality

LC 50 (Water flea (Daphnia magna), 96 h): > 100 mg/l Mortality

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability



Revision Date: 08/05/2016

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Acetone Log Kow: -0.24

Propane Log Kow: 2.36

Butane Log Kow: 2.89

Isobutane Log Kow: 2.76

Mobility in Soil: No data available.

Other Adverse Effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

UN1950, AEROSOLS, 2.1

CFR / DOT:

UN1950, Aerosols, 2.1

IMDG:

UN1950, AEROSOLS, 2.1

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.



Revision Date: 08/05/2016

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Acetone	5000 lbs.
Propane	100 lbs.
Butane	100 lbs.
Isobutane	100 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification Chemical Identity Reportable quantity

Chemical lucitury	nepultable q
Acetone	5000 lbs.
Propane	100 lbs.
Butane	100 lbs.
Isobutane	100 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u> <u>Threshold Planning Quantity</u>

Acetone 500 lbs
Propane 500 lbs
Butane 500 lbs
Isobutane 500 lbs

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

	= =
Chemical Identity	Reportable quantity
Propane	10000 lbs
Butane	10000 lbs
Isobutane	10000 lbs



Revision Date: 08/05/2016

US State Regulations

US. California Proposition 65

No ingredient regulated by CA Prop 65 present.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Acetone Propane

Butane Isobutane

US. Massachusetts RTK - Substance List

Chemical Identity

Acetone Propane Butane

Isobutane

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Acetone Propane Butane

Isobutane

US. Rhode Island RTK

Chemical Identity

Acetone

Propane

Butane

Isobutane

Other Regulations:

Regulatory VOC (less water 551 g/l

and exempt solvent):

VOC Method 310: 30.00 %

Inventory Status:

Australia AICS: All components in this product are listed on or

exempt from the Inventory.

Canada DSL Inventory List:

All components in this product are listed on or

exempt from the Inventory.

EINECS, ELINCS or NLP: All components in this product are listed on or

exempt from the Inventory.

Japan (ENCS) List: All components in this product are listed on or

exempt from the Inventory.

China Inv. Existing Chemical Substances: All components in this product are listed on or



Revision Date: 08/05/2016

exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI): All components in this product are listed on or

exempt from the Inventory.

Canada NDSL Inventory: One or more components in this product are

not listed on or exempt from the Inventory.

Philippines PICCS: All components in this product are listed on or

exempt from the Inventory.

US TSCA Inventory: All components in this product are listed on or

exempt from the Inventory.

New Zealand Inventory of Chemicals:

All components in this product are listed on or

exempt from the Inventory.

Japan ISHL Listing:

All components in this product are listed on or

exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are

not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date: 08/05/2016

Version #: 1.2

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.