
PRODUCT DESCRIPTION

Gutter Seal is a one-part, high quality blend of synthetic rubber and resin. It exhibits excellent elastomeric properties while maintaining superior adhesion under ponded water conditions.

BASIC USES

Gutter Seal has been specifically designed for use in gutter and rainwater applications. It is ideally suited for metal-to-metal and metal-to-plastic joinery, commonly found in and around the eavestrough.

FEATURES & BENEFITS

Gutter Seal is easy to apply with conventional caulking equipment and offers excellent elastomeric properties. Gutter Seal maintains its superior adhesion capabilities even under ponded water conditions.

Should the Gutter Seal be damaged, it can be repaired. Please contact your local Tremco Sales Representative or Tremco Technical Services for repair procedures.

AVAILABILITY

Immediately available from your local Tremco Sales Representative, Tremco Distributor, or Tremco Warehouse in 10.1 oz (300 mL) cartridges, packed 30 per case.

COLORS

Gutter Seal is available in Clear and White.

LIMITATIONS

Gutter Seal should not be applied to damp or contaminated surfaces. Do not subject Gutter Seal to more than 20% movement or expansion.

WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL RESULTS
Rheological Properties	ASTM C639	0 flow, no deformation
Extrusion Rate	ASTM C661	Pass
Hardness Properties	ASTM C661	20 to 30
Sag Resistance	ASTM C639	< 1/8" (< 3.0 mm)
Weight Loss	ASTM C679	9 %
Skin Time	ASTM C679	5 to 10 min
Tack Free Time	73.4°F (23°C) 50% RH	30 min
Stain and Color Change	ASTM C510	No visible color change, no stain

Adhesion to Aluminum	ASTM C794	11 to 12 pli (2.0 kN/m)
Adhesion to Wood	ASTM C794	15 to 17 pli (3.0 kN/m)
Adhesion to PVC	ASTM C794	15 to 17 pli (3.0 kN/m)
Effects to Accelerated Aging	ASTM C793	Passes
Movement Capability	ASTM C719	± 12.5 %

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

GUTTER-DS/1222

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



tremcosealants.com | 800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com