

SAFETY DATA SHEET

1. Identification

Material name: GUTTER SEAL WHITE 30 CTG/CASE
Material: 984806T 323

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants
220 Wicksteed Ave
Toronto ON M4H 1G7
CA

Contact person: EH&S Department
Telephone: 1-800-263-6046
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable solid Category 1

Health Hazards

Acute toxicity (Inhalation - vapor) Category 4
Acute toxicity (Inhalation - dust and mist) Category 4
Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2B
Carcinogenicity Category 2
Toxic to reproduction Category 2
Specific Target Organ Toxicity - Repeated Exposure Category 2¹

Target Organs

1. hearing

Unknown toxicity - Health

Acute toxicity, oral 30.45 %
Acute toxicity, dermal 38.59 %
Acute toxicity, inhalation, vapor 68.81 %
Acute toxicity, inhalation, dust or mist 68.55 %

Environmental Hazards

Acute hazards to the aquatic environment

Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic environment	61.03 %
Chronic hazards to the aquatic environment	99.98 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Flammable solid.
Harmful if inhaled.
Causes skin and eye irritation.
Suspected of causing cancer.
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure.
Harmful to aquatic life.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/...] equipment. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid release to the environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water/... If skin irritation occurs: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing. In case of fire: Use... to extinguish.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Xylene	1330-20-7	10 - <25%
Titanium dioxide	13463-67-7	5 - <10%
Ethylbenzene	100-41-4	5 - <10%
Aluminum oxide	1344-28-1	0.1 - <1%
Toluene	108-88-3	0.1 - <1%
Butylated hydroxytoluene	128-37-0	0.1 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Description of necessary first-aid measures

- Inhalation:** Move to fresh air.
- Skin Contact:** Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.
- Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.
- Ingestion:** Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
- Personal Protection for First-aid Responders:** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Most important symptoms/effects, acute and delayed

- Symptoms:** Respiratory tract irritation. Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping.
- Hazards:** No data available.

Indication of immediate medical attention and special treatment needed

- Treatment:** Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Accidental release measures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Methods and material for containment and cleaning up: Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Handling

Technical measures (e.g. Local and general ventilation): Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Safe handling advice: Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Avoid contact with skin.

Contact avoidance measures: No data available.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Avoid contact with skin.

Storage

Safe storage conditions: Store locked up. Store in a cool place.

Safe packaging materials: No data available.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	100 ppm 435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	100 ppm 435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
	STEL	150 ppm 655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
	ST ESL	350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (07 2011)
	ST ESL	80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (07 2011)
	AN ESL	42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (07 2011)
	AN ESL	180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as

			amended (07 2011)
	STEL	150 ppm 655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (08 2010)
	Ceiling	300 ppm	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (08 2010)
	TWA PEL	100 ppm 435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (08 2010)
	TWA	100 ppm	US. ACGIH Threshold Limit Values, as amended (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values, as amended (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Titanium dioxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Titanium dioxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values, as amended (2011)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Aluminum oxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Aluminum oxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Aluminum oxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Toluene	TWA	20 ppm	US. ACGIH Threshold Limit Values, as amended (2011)
	TWA	200 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000), as amended (02 2006)
	Ceiling	300 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000), as amended (02 2006)
	MAX. CONC	500 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000), as amended (02 2006)
Butylated hydroxytoluene - Inhalable fraction and vapor.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)

Chemical name	Type	Exposure Limit Values	Source
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Xylene	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Trade Secret - Total dust.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Ethylbenzene	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)

Toluene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Toluene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Toluene	TWA	50 ppm 188 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)

Chemical name	Type	Exposure Limit Values	Source
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Xylene	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Trade Secret - Total dust.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)

Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Ethylbenzene	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)

Aluminum oxide - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Aluminum oxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Aluminum oxide - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Aluminum oxide - Total dust. - as Al	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Toluene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Toluene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Toluene	TWA	50 ppm 188 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Butylated hydroxytoluene - Vapor and aerosol, inhalable.	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Butylated hydroxytoluene - Inhalable fraction and vapor.	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Butylated hydroxytoluene	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Zirconium dioxide - as Zr	STEL	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Zirconium dioxide - as Zr	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Zirconium dioxide - as Zr	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)

Amorphous silica - Total	TWA	4 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable.	TWA	1.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable dust.	TWA	6 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Silica gel desiccant - Respirable dust.	TWA	6 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Diisodecyl phthalate	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Methanol	STEL	250 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	200 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methanol	STEL	250 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	TWA	200 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Methanol	STEL	250 ppm 328 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	TWA	200 ppm 262 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Benzene	STEL	2.5 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.5 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Benzene	TWA	0.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
	STEL	2.5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Benzene	TWA	1 ppm 3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	STEL	5 ppm 15.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)
Toluene (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEI (03 2013)
Toluene (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEI (03 2013)
Toluene (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEI (03 2013)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

- General information:** Use explosion-proof ventilation equipment. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide easy access to water supply and eye wash facilities.
- Eye/face protection:** Wear safety glasses with side shields (or goggles).
- Skin Protection**
- Hand Protection:** Use suitable protective gloves if risk of skin contact.
- Other:** Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
- Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
- Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Avoid contact with skin.

9. Physical and chemical properties

Appearance

- Physical state:** solid
- Form:** Paste

Color:	White
Odor:	Strong petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	Yes
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.05
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates).
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation: In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.

Skin Contact:	May be harmful in contact with skin. Causes skin irritation.
Eye contact:	Causes eye irritation.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects**Acute toxicity (list all possible routes of exposure)****Oral**

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Xylene	LD 50 (Rat): 3,523 mg/kg
Titanium dioxide	LD 50 (Rat): > 5,000 mg/kg
Ethylbenzene	LD 50 (Rat): 3,500 mg/kg
Aluminum oxide	LD 50 (Rat): > 10,000 mg/kg
Toluene	LD 50 (Rat): 5,580 mg/kg
Butylated hydroxytoluene	LD 50 (Rat): 890 mg/kg

Dermal

Product: ATEmix: 2,707.13 mg/kg

Inhalation

Product: ATEmix: 11.11 mg/l
ATEmix : 1.53 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Xylene	in vivo (Rabbit): Moderate irritant
Titanium dioxide	in vivo (Rabbit): Not irritant
Aluminum oxide	in vivo (Rabbit): Not irritant
Toluene	in vivo (Rabbit): Irritating
Butylated hydroxytoluene	in vivo (Rabbit): Not irritant

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Xylene	Rabbit, 24 hrs: Moderately irritating
Titanium dioxide	Rabbit, 24 hrs: Not irritating
Ethylbenzene	Rabbit, 7 d: Slightly irritating
Aluminum oxide	Rabbit, 24 hrs: Not irritating
Toluene	Rabbit, 24 - 72 hrs: Not irritating
Butylated hydroxytoluene	Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: Suspected of causing cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity

Product: Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Target Organs

Specific Target Organ Toxicity - Repeated Exposure: hearing

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information**Ecotoxicity:****Acute hazards to the aquatic environment:****Fish**

Product: No data available.

Specified substance(s):

Xylene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality

Ethylbenzene LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality

Toluene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 20.5 - 23.8 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication
Toluene	LC 50 (Water flea (Daphnia magna), 24 h): 240 - 420 mg/l Mortality
Butylated hydroxytoluene	EC 50 (Water flea (Daphnia pulex), 48 h): 1.44 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Toluene
 LOAEL (Oncorhynchus kisutch, 40 d): 2.77 mg/l Experimental result, Key study
 NOAEL (Pimephales promelas, 32 d): 4 mg/l Experimental result, Supporting study
 LOAEL (Pimephales promelas, 32 d): 6 mg/l Experimental result, Supporting study
 NOAEL (Oncorhynchus kisutch, 40 d): 1.39 mg/l Experimental result, Key study

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Toluene
 Green algae (Selenastrum capricornutum), Bioconcentration Factor (BCF): 3,016 (Static)

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Xylene
 Log Kow: 3.12 - 3.20

Ethylbenzene
 Log Kow: 3.15

Toluene

Log Kow: 2.73

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal methods: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

UN3175, SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Xylene), 4.1, PG II

CFR / DOT:

UN3175, Solids containing flammable liquid, n.o.s. (Xylene), 4.1, PG II

IMDG:

UN3175, SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Xylene), 4.1, PG II

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Benzene	Blood respiratory tract irritation Central nervous system Flammability Cancer Skin Aspiration Eye

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.
Benzene	10 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

- Fire Hazard
- Immediate (Acute) Health Hazards
- Delayed (Chronic) Health Hazard
- Flammable (gases, aerosols, liquids, or solids)
- Acute toxicity (any route or exposure)
- Skin Corrosion or Irritation
- Serious eye damage or eye irritation
- Carcinogenicity
- Reproductive toxicity
- Specific target organ toxicity (single or repeated exposure)

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

None present or none present in regulated quantities.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
--------------------------	------------------------------------

SARA 313 (TRI Reporting)

Chemical Identity

Xylene
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	Reportable quantity: lbs.

US State Regulations

US. California Proposition 65



WARNING

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Xylene
Titanium dioxide
Ethylbenzene

US. Massachusetts RTK - Substance List

Chemical Identity

Xylene
Titanium dioxide
Ethylbenzene

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Xylene
Titanium dioxide
Ethylbenzene

US. Rhode Island RTK

Chemical Identity

Xylene
Titanium dioxide
Ethylbenzene

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and
exempt solvent) : 328 g/l

VOC Method 310 : 31.20 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	All components in this product are listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision
--

Revision Date: 11/04/2019

Version #: 1.1

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.