

We certify that Proglaze® has been tested against ASTM C 920, Standard Specification for Elastomeric Joint Sealants and does conform to the specification requirements and is classified as follows:

Type: S	(Single Component)
Grade: NS	(Non-sag)
Class: 25	(+/- 25% joint movement)
Use: NT	(Non-traffic)
G	(Glass)
A	(Aluminum)
O	(Other)

We further certify that Proglaze conforms to the requirements of the following Federal Specifications:  
TT-S-00230C (COM-NBS), Type II, Class A

***TT-S-001543A (COM-NBS) Class A***

Proglaze meets CAN/CGSB-19.13-M87, MG-2-25-A-L.

Although Proglaze is not NSF registered, or previously authorized by USDA, it does meet the requirements for use in Federally inspected food processing facilities provided it is not used in areas where food is being processed, prepared or packaged. The material must also be applied in a manner which prevents any direct or indirect contamination of food. Additionally, before any food product can be placed in the area of treatment, the sealant must be allowed to cure according to manufacturer's recommendations and the area should be sufficiently free of odor to prevent food contamination.

Proglaze may be used in registered establishments operating under the **Canadian Food Inspection Agency**. The Canadian Food Inspection Agency has approved Proglaze for use in CFIA regulated facilities for situations involving non food contact.