

# Tremco® Reemay

Reinforcing Fabric 2011

# **Product Description**

A spun-bonded polyester fabric style 2011, consisting of a nonwoven fabric of continuous filament polyester fibers that are randomly arranged. These fibers are highly dispersed and bonded at the filament junctions.

#### **Basic Uses**

Tremco® Reinforcing Fabric is used to reinforce hot fluid-applied membranes in multi-lift applications.

### **Availability**

Immediately available from your local Tremco Sales Representative or Tremco Distributor. For Distributor locations visit www.tremcosealants.com.

# **Packaging**

84 in. x 675 ft. (2.13m x 205.74 m) roll

36 in. x 600 ft. (0.91m x 183m) roll

12 in. x 600 ft. (30cm x 183m) roll

## **Warranty**

Tremco warrants its Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of Tremco Product proven to be defective, and Tremco shall not be liable for any loss or damage.

Please refer to our website at <a href="www.tremcosealants.com">www.tremcosealants.com</a> for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TYPICAL PHYSICAL PROPERTIES		
PROPERTY	TEST METHOD	TYPICAL VALUES
Color		White
Weight	ASTM D3776	0.75 oz/y2 (25 gsm)
Thickness (Mil)	ASTM D1777	8.0 mil (0.20 mm)
Sheet Grab Tensile (lb - MD x XD)	ASTM D4632	15.4 lbs x 11.2 lbs (69 x 50 N)
Trapezoid Tear (lb - MD x XD)	ASTM D1117	4.9 lbs x 5.8 lbs (21.8 x 25.8 N)

