



Tremco Commercial Sealants & Waterproofing
3735 Green Road
Beachwood, OH 44122
US: 800.852.9068
Canada: 800.363.3213
www.tremcosealants.com

We certify that Spectrem® 2 has been tested against ASTM C 920, Standard Specification for Elastomeric Joint Sealants and does conform to the specification requirements and is classified as follows:

Type:	S	(Single Component)
Grade:	NS	(Non-sag)
Class:	50	(+/- 50% joint movement)
Use:	NT	(Non-traffic)
	M	(Mortar)
	G	(Glass)
	A	(Aluminum)
	O	(Other)

Spectrem 2 meets and exceeds the requirements of ASTM C 1184, Standard Specification for Structural Silicone Sealants. Silicone sealants are required to meet minimum physical properties which include a Shore A hardness range of 20-60, maximum tack free time of 3 hrs and a minimum tensile value of 50 psi when tested at the following conditions including, standard conditions, 80C(190F), -29 C (-20F) water immersion, and 5000hrs weathering.

Spectrem 2 Black is listed to AAMA 800-92, Voluntary Specifications and Test Methods for Sealants, for Section 1.1, Back Bedding Glazing Compounds, 802.3 Types I and II, Section 1.1, Back Bedding Glazing Compounds, 805.2-92 (Group C), and Section 1.4, Exterior Perimeter Sealing Compound, 808.3.

Spectrem 2 has been tested and passed ASTM C 1382, "Standard Test Method for Determining Tensile Adhesion Properties of Sealants when used in Exterior Insulation and Finish Systems (EIFS) Joints." Third party verification is available upon request.

We further certify that Spectrem 2 conforms to the requirements of the following Federal Specifications:
TT-S-00230C (COM-NBS), Type II, Class A

Spectrem 2 meets CAN/CGSB-19.13-M87.

Spectrem 2 meets the Chinese Specification GB-16776.

Spectrem 2 meets the European Organization for Technical Approval (EOTA) specification ETAG-002, Structural Sealant Glazing Systems.

Spectrem 2 may be used in official establishments operating under the United States Department of Agriculture Federal Meat and Poultry products inspection program. Tremco certifies Spectrem 2 meets the compositional requirements for use in USDA regulated facilities for situations involving incidental food contact provided the sealant be used in a manner that prevents indirect contamination of edible products. The sealant must be allowed to cure according to manufacturer's recommendations prior to any indirect food contact. The sealant does not contain antimony, arsenic, cadmium, selenium, carcinogens, mutagens or teratogens. Spectrem 2 may be used in registered establishments operating under the Canadian Food Inspection Agency. The Canadian Food Inspection Agency has approved Spectrem 2 for use in CFIA regulated facilities for situations involving non food contact.

Rev. 05/17/2024