

Tremco Incorporated certifies that TREMDrain 6000 multi-composite drainage and protection boards meet the physical properties outlined in the Tremco Incorporated published data sheets, specifications, and application instructions. This product has been tested against the following ASTM methods as shown herein:

TREMDrain® 6000

Multi-Composite Drainage and Protection Boards

TYPICAL PHYSICAL PROPERTIES

| PROPERTY | TEST METHOD | VALUES US | VALUES SI |
|------------------------------|-------------|---------------------------|---------------------------|
| Typical Applications | | | |
| Flow Capacity per unit width | ASTM D4716 | 18 gpm/ft | 224 Lpm/M |
| Roll Length | | 50' | 15.24 M |
| Roll Width | | 6' | 1.8 M |
| Fabric | | | |
| Material | | Polypropylene | |
| Weight | ASTM D3776 | | |
| Grab Tensile Strength | ASTM D4632 | 115 lbf | 512 N |
| Puncture Strength | ASTM D4833 | 70 lb | 311 N |
| Trapezoidal Tear | ASTM D4533 | | |
| Mullen Burst Strength | ASTM D3786 | | |
| Grab Elongation | ASTM D4632 | 70% | |
| AOS | ASTM D4751 | 70 sieve | 0.21 mm |
| Flow Rate | ASTM D4491 | 150 gpm/ft ² | 6,6116 Lpm/M ² |
| Root Barrier Fabric | | None | |
| UV Resistance | ASTM D4355 | 70% / 500 hr | |
| Core | | | |
| Material | | Polypropylene | |
| Thickness | ASTM D1777 | 0.4" | |
| Compressive Strength | | 15,000 lb/ft ² | 718 kPa |