

TREMDrain 6600 SERIES DRAINAGE MAT
ADHERED WITH CONTINUOUS 80 MIL
COURSE OF TREMproof 6100

MINIMUM 2 INCH THICK
CONCRETE PAVERS

MINIMUM 2 INCH THICK
MORTAR BED

TREMCO QD
LOW ODOR PRIMER

215 mils TREMproof 6100 HOT RUBBERIZED
ASPHALT WATERPROOFING MEMBRANE
WITH EMBEDDED REINFORCEMENT FABRIC

TREMCO POWERPLY STANDARD GRANULAR

NOTES:

1. PROPER APPLICATION IS THE RESPONSIBILITY OF THE INSTALLATION PROFESSIONAL. SURFACE PREPARATION, SUBSTRATE ADHESION, PROPER INSTALLATION AND OTHER VARIABLES OUTSIDE OF THE MANUFACTURER'S CONTROL ARE THE SOLE RESPONSIBILITY OF THE USER. FIELD VISITS BY TREMCO PERSONNEL ARE FOR THE PURPOSE OF MAKING TECHNICAL RECOMMENDATIONS, NOT FOR SUPERVISING OR PROVIDING QUALITY CONTROL.
2. TREMCO CANNOT BE RESPONSIBLE FOR MATERIAL DIFFERENCES, SUBSTITUTIONS, OR DAY-TO-DAY VARIATIONS IN THE FINISHING PROCESS THAT MAY ALTER THESE RECOMMENDATIONS/RESULTS.

Rev	Date	Description	By
-	-	-	-

Rev #
00

File Name:
6100-1

Sheet Number:

Date: 09/10/14

TREMPROOF 6100

Scale: None

Checked by: JB

Drawn by: JB

TREMCO
www.tremcosolutions.com

3735 Green Road • Beachwood, OH 44122
Phone : 866-209-2404 • Fax: 216-766-5535