

SAFETY DATA SHEET

1. Identification

Material name: TREMPROOF 260
Material: 582100 855

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

| | |
|-----------------|-------------|
| Skin sensitizer | Category 1 |
| Carcinogenicity | Category 1A |

Unknown toxicity - Health

| | |
|--|---------|
| Acute toxicity, oral | 4.1 % |
| Acute toxicity, dermal | 4.27 % |
| Acute toxicity, inhalation, vapor | 69.1 % |
| Acute toxicity, inhalation, dust or mist | 64.44 % |

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: May cause an allergic skin reaction.
May cause cancer.

Precautionary Statements

- Prevention:** Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
- Response:** IF ON SKIN: Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse.
- Storage:** Store locked up.
- Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

| Chemical Identity | CAS number | Content in percent (%)* |
|-----------------------|------------|-------------------------|
| Asphalt | 8052-42-4 | 20 - <50% |
| Oxidized asphalt | 64742-93-4 | 5 - <10% |
| Paraffinic distillate | 64742-04-7 | 1 - <5% |
| Petroleum distillates | 64742-47-8 | 1 - <5% |
| Aliphatic naphtha | 64742-88-7 | 1 - <5% |
| Wood rosin | 8050-09-7 | 0.1 - <1% |
| Xylene | 1330-20-7 | 0.1 - <1% |
| Sodium hydroxide | 1310-73-2 | 0.1 - <1% |

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
- Inhalation:** Move to fresh air.
- Skin Contact:** If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact: Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

| Chemical Identity | Type | Exposure Limit Values | Source |
|---|--------|-------------------------------|---|
| Asphalt - Inhalable fraction. - as benzene solubles | TWA | 0.5 mg/m ³ | US. ACGIH Threshold Limit Values (2011) |
| Paraffinic distillate - Mist. | PEL | 5 mg/m ³ | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor | TWA | 200 mg/m ³ | US. ACGIH Threshold Limit Values (2011) |
| | TWA | 200 mg/m ³ | US. ACGIH Threshold Limit Values (2011) |
| Aliphatic naphtha - Non-aerosol. - as total hydrocarbon vapor | TWA | 200 mg/m ³ | US. ACGIH Threshold Limit Values (03 2014) |
| Aliphatic naphtha | PEL | 100 ppm 400 mg/m ³ | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (01 2017) |
| Xylene | STEL | 150 ppm 655 mg/m ³ | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| | REL | 100 ppm 435 mg/m ³ | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| | STEL | 150 ppm 655 mg/m ³ | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| | REL | 100 ppm 435 mg/m ³ | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| | STEL | 150 ppm 655 mg/m ³ | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| | REL | 100 ppm 435 mg/m ³ | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| | STEL | 150 ppm 655 mg/m ³ | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | TWA | 100 ppm 435 mg/m ³ | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | TWA | 100 ppm 435 mg/m ³ | US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008) |
| | STEL | 150 ppm 655 mg/m ³ | US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008) |
| | ST ESL | 350 µg/m ³ | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011) |
| | ST ESL | 80 ppb | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011) |
| | AN ESL | 42 ppb | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011) |
| | AN ESL | 180 µg/m ³ | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011) |

| | | | |
|------------------|---------|-------------------|--|
| | | | 2011) |
| | STEL | 150 ppm 655 mg/m3 | US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010) |
| | Ceiling | 300 ppm | US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010) |
| | TWA PEL | 100 ppm 435 mg/m3 | US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010) |
| | TWA | 100 ppm | US. ACGIH Threshold Limit Values (2011) |
| | STEL | 150 ppm | US. ACGIH Threshold Limit Values (2011) |
| | PEL | 100 ppm 435 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Sodium hydroxide | Ceiling | 2 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| | PEL | 2 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |

| Chemical name | Type | Exposure Limit Values | Source |
|---|------|-----------------------|---|
| Asphalt - Aerosol, inhalable. - as benzene solubles | TWA | 0.5 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Asphalt - Inhalable fraction. - as benzene solubles | TWA | 0.5 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Asphalt - Fume. | TWA | 5 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor | TWA | 200 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Petroleum distillates | TWA | 525 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor | TWA | 200 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| | TWA | 200 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |

| Chemical name | Type | Exposure Limit Values | Source |
|---|------|-----------------------|---|
| Asphalt - Aerosol, inhalable. - as benzene solubles | TWA | 0.5 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Asphalt - Inhalable fraction. - as benzene solubles | TWA | 0.5 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Asphalt - Fume. | TWA | 5 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Paraffinic distillate - Mist. | TWA | 0.2 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013) |
| Paraffinic distillate - Inhalable fraction. | TWA | 5 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Paraffinic distillate - Mist. | TWA | 5 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| | STEL | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |

| | | | |
|---|------|---------------------|---|
| Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor | TWA | 200 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Petroleum distillates | TWA | 525 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor | TWA | 200 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| | TWA | 200 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Aliphatic naphtha - Non-aerosol. - as total hydrocarbon vapor | TWA | 200 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013) |
| Aliphatic naphtha - Non-aerosol. - as total hydrocarbon vapor | TWA | 200 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Aliphatic naphtha | TWA | 400 ppm 1,590 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Wood rosin - as formaldehyde | TWA | 0.1 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Xylene | TWA | 100 ppm 434 mg/m3 | Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009) |
| | STEL | 150 ppm 651 mg/m3 | Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009) |
| Xylene | TWA | 100 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | STEL | 150 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Xylene | TWA | 100 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| | STEL | 150 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Xylene | STEL | 150 ppm 651 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| | TWA | 100 ppm 434 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |

| | | | |
|--------------------|---------|---------------------|---|
| Sodium hydroxide | CEILING | 2 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Sodium hydroxide | CEV | 2 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Sodium hydroxide | CEILING | 2 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Nonane | TWA | 200 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013) |
| Nonane | TWA | 200 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Nonane | TWA | 200 ppm 1,050 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |
| Ammonium hydroxide | STEL | 35 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | TWA | 25 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Ammonium hydroxide | TWA | 25 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| | STEL | 35 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Toluene | TWA | 20 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Toluene | TWA | 20 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Toluene | TWA | 50 ppm 188 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Ethylbenzene | TWA | 20 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011) |
| Ethylbenzene | TWA | 20 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Ethylbenzene | STEL | 125 ppm 543 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| | TWA | 100 ppm 434 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Naphthalene | STEL | 15 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | TWA | 10 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Naphthalene | TWA | 10 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| | STEL | 15 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |

| | | | | |
|------------------|---------|---------|------------|---|
| Naphthalene | TWA | 10 ppm | 52 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| | STEL | 15 ppm | 79 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Benzene | STEL | 2.5 ppm | | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | TWA | 0.5 ppm | | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Benzene | TWA | 0.5 ppm | | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| | STEL | 2.5 ppm | | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Benzene | TWA | 1 ppm | 3 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| | STEL | 5 ppm | 15.5 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Cumene | STEL | 75 ppm | | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | TWA | 25 ppm | | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Cumene | TWA | 50 ppm | | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Cumene | TWA | 50 ppm | 246 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Ethyl Acrylate | TWA | 5 ppm | | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | STEL | 15 ppm | | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Ethyl Acrylate | TWA | 5 ppm | | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| | STEL | 15 ppm | | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Ethyl Acrylate | STEL | 15 ppm | 61 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| | TWA | 5 ppm | 20 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Hydrogen sulfide | CEILING | 10 ppm | | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Hydrogen sulfide | STEL | 15 ppm | | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| | TWA | 10 ppm | | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |

| | | | | |
|------------------|------|--------|----------|--|
| Hydrogen sulfide | TWA | 10 ppm | 14 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| | STEL | 15 ppm | 21 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |

Biological Limit Values

| Chemical Identity | Exposure Limit Values | Source |
|---|-------------------------------|---------------------|
| Xylene (Methylhippuric acids: Sampling time: End of shift.) | 1.5 g/g (Creatinine in urine) | ACGIH BEI (03 2013) |

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

- General information:** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
- Eye/face protection:** Wear safety glasses with side shields (or goggles).
- Skin Protection**
- Hand Protection:** Use suitable protective gloves if risk of skin contact.
- Other:** Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
- Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
- Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

- Physical state:** liquid
- Form:** liquid
- Color:** Brown
- Odor:** Slight odor
- Odor threshold:** No data available.
- pH:** 9 - 10.5
- Melting point/freezing point:** No data available.
- Initial boiling point and boiling range:** No data available.

| | |
|--|---|
| Flash Point: | > 93 °C > 200 °F (Setaflash Closed Cup) |
| Evaporation rate: | Slower than Ether |
| Flammability (solid, gas): | No |
| Upper/lower limit on flammability or explosive limits | |
| Flammability limit - upper (%): | No data available. |
| Flammability limit - lower (%): | No data available. |
| Explosive limit - upper (%): | No data available. |
| Explosive limit - lower (%): | No data available. |
| Vapor pressure: | 23.76 hPa |
| Vapor density: | Vapors are heavier than air and may travel along the floor and in the bottom of containers. |
| Relative density: | 0.99 |
| Solubility(ies) | |
| Solubility in water: | Dispersible |
| Solubility (other): | No data available. |
| Partition coefficient (n-octanol/water): | No data available. |
| Auto-ignition temperature: | No data available. |
| Decomposition temperature: | No data available. |
| Viscosity: | No data available. |

10. Stability and reactivity

| | |
|--|---|
| Reactivity: | No data available. |
| Chemical Stability: | Material is stable under normal conditions. |
| Possibility of hazardous reactions: | No data available. |
| Conditions to avoid: | Avoid heat or contamination. |
| Incompatible Materials: | Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). |
| Hazardous Decomposition Products: | Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors. |

11. Toxicological information

Information on likely routes of exposure

| | |
|----------------------|--|
| Inhalation: | In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes. |
| Skin Contact: | May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction. |
| Eye contact: | Eye contact is possible and should be avoided. |
| Ingestion: | May be ingested by accident. Ingestion may cause irritation and malaise. |

Symptoms related to the physical, chemical and toxicological characteristics

| | |
|----------------------|--------------------|
| Inhalation: | No data available. |
| Skin Contact: | No data available. |
| Eye contact: | No data available. |
| Ingestion: | No data available. |

Information on toxicological effects**Acute toxicity (list all possible routes of exposure)**

| | |
|--------------------------------------|--|
| Oral Product: | Not classified for acute toxicity based on available data. |
| Dermal Product: | Not classified for acute toxicity based on available data. |
| Inhalation Product: | ATEmix: 65.62 mg/l |

| | |
|--|--------------------|
| Repeated dose toxicity Product: | No data available. |
|--|--------------------|

| | |
|---|--------------------|
| Skin Corrosion/Irritation Product: | No data available. |
|---|--------------------|

| | |
|---|--------------------|
| Serious Eye Damage/Eye Irritation Product: | No data available. |
|---|--------------------|

| | |
|---|--------------------|
| Respiratory or Skin Sensitization Product: | No data available. |
|---|--------------------|

| | |
|---|--------------------|
| Carcinogenicity Product: | No data available. |
|---|--------------------|

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

| | |
|-----------------------|--|
| Asphalt | Overall evaluation: Possibly carcinogenic to humans. |
| Oxidized asphalt | Overall evaluation: Probably carcinogenic to humans. |
| Paraffinic distillate | Overall evaluation: Carcinogenic to humans. |

US. National Toxicology Program (NTP) Report on Carcinogens:

| | |
|-----------------------|-------------------------------|
| Paraffinic distillate | Known To Be Human Carcinogen. |
|-----------------------|-------------------------------|

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):
No carcinogenic components identified**Germ Cell Mutagenicity**

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information**Ecotoxicity:****Acute hazards to the aquatic environment:**

Fish
Product: No data available.

Aquatic Invertebrates
Product: No data available.

Chronic hazards to the aquatic environment:

Fish
Product: No data available.

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants
Product: No data available.

Persistence and Degradability

Biodegradation
Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential
Bioconcentration Factor (BCF)
Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product: No data available.

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

| <u>Chemical Identity</u> | <u>OSHA hazard(s)</u> |
|--------------------------|--|
| Benzene | Blood respiratory tract irritation Central nervous system Flammability Cancer Skin Aspiration Eye |

CERCLA Hazardous Substance List (40 CFR 302.4):

| <u>Chemical Identity</u> | <u>Reportable quantity</u> |
|--------------------------|----------------------------|
| Asphalt | 100 lbs. |
| Xylene | 100 lbs. |
| Sodium hydroxide | 1000 lbs. |
| Nonane | 100 lbs. |
| Ammonium hydroxide | 1000 lbs. |
| Toluene | 1000 lbs. |
| Ethylbenzene | 1000 lbs. |
| Naphthalene | 100 lbs. |
| Benzene | 10 lbs. |
| Cumene | 5000 lbs. |
| Ethyl Acrylate | 1000 lbs. |
| Hydrogen sulfide | 100 lbs. |

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards
Delayed (Chronic) Health Hazard
Respiratory or Skin Sensitization
Carcinogenicity

SARA 302 Extremely Hazardous Substance

| <u>Chemical Identity</u> | <u>Reportable quantity</u> | <u>Threshold Planning Quantity</u> |
|--------------------------|----------------------------|------------------------------------|
| Hydrogen sulfide | 100 lbs. | 500 lbs. |

SARA 304 Emergency Release Notification

| <u>Chemical Identity</u> | <u>Reportable quantity</u> |
|--------------------------|----------------------------|
| Asphalt | 100 lbs. |
| Xylene | 100 lbs. |
| Sodium hydroxide | 1000 lbs. |
| Nonane | 100 lbs. |
| Ammonium hydroxide | 1000 lbs. |
| Toluene | 1000 lbs. |
| Ethylbenzene | 1000 lbs. |
| Naphthalene | 100 lbs. |
| Benzene | 10 lbs. |
| Cumene | 5000 lbs. |
| Ethyl Acrylate | 1000 lbs. |
| Hydrogen sulfide | 100 lbs. |

SARA 311/312 Hazardous Chemical

| <u>Chemical Identity</u> | <u>Threshold Planning Quantity</u> |
|--------------------------|------------------------------------|
| Hydrogen sulfide | 500lbs |
| Asphalt | 10000 lbs |
| Oxidized asphalt | 10000 lbs |
| Paraffinic distillate | 10000 lbs |
| Petroleum distillates | 10000 lbs |
| Aliphatic naphtha | 10000 lbs |
| Wood rosin | 10000 lbs |
| Xylene | 10000 lbs |
| Sodium hydroxide | 10000 lbs |

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

| <u>Chemical Identity</u> | <u>Reportable quantity</u> |
|--------------------------|----------------------------|
| Hydrogen sulfide | lbs |

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

| <u>Chemical Identity</u> | <u>Reportable quantity</u> |
|--------------------------|----------------------------|
| Xylene | Reportable quantity: lbs. |

US State Regulations

US. California Proposition 65



WARNING

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

| <u>Chemical Identity</u> |
|--------------------------|
| Asphalt |
| Oxidized asphalt |
| Paraffinic distillate |
| Petroleum distillates |
| Aliphatic naphtha |

US. Massachusetts RTK - Substance List

Chemical Identity

Asphalt
Paraffinic distillate
Petroleum distillates
Aliphatic naphtha
Benzene
Ethyl Acrylate

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Asphalt
Oxidized asphalt
Paraffinic distillate
Petroleum distillates
Aliphatic naphtha

US. Rhode Island RTK

Chemical Identity

Asphalt
Paraffinic distillate
Petroleum distillates
Aliphatic naphtha

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and
exempt solvent) : 70 g/l

VOC Method 310 : 4.93 %

Inventory Status:

| | |
|--|--|
| Australia AICS: | One or more components in this product are not listed on or exempt from the Inventory. |
| Canada DSL Inventory List: | All components in this product are listed on or exempt from the Inventory. |
| EINECS, ELINCS or NLP: | One or more components in this product are not listed on or exempt from the Inventory. |
| Japan (ENCS) List: | One or more components in this product are not listed on or exempt from the Inventory. |
| China Inv. Existing Chemical Substances: | One or more components in this product are not listed on or exempt from the Inventory. |
| Korea Existing Chemicals Inv. (KECI): | One or more components in this product are not listed on or exempt from the Inventory. |
| Canada NDSL Inventory: | One or more components in this product are not listed on or exempt from the Inventory. |
| Philippines PICCS: | One or more components in this product are not listed on or exempt from the Inventory. |
| US TSCA Inventory: | All components in this product are listed on or exempt from the Inventory. |
| New Zealand Inventory of Chemicals: | One or more components in this product are not listed on or exempt from the Inventory. |
| Japan ISHL Listing: | One or more components in this product are not listed on or exempt from the Inventory. |
| Japan Pharmacopoeia Listing: | One or more components in this product are not listed on or exempt from the Inventory. |
| Mexico INSQ: | One or more components in this product are not listed on or exempt from the Inventory. |
| Ontario Inventory: | One or more components in this product are not listed on or exempt from the Inventory. |
| Taiwan Chemical Substance Inventory: | One or more components in this product are not listed on or exempt from the Inventory. |

16. Other information, including date of preparation or last revision**Revision Date:** 07/21/2018**Version #:** 1.2**Further Information:** No data available.**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.